


## 150W LED Highbay Fixture

Order Code: HB95488

## DLC Model# HW-150C-AB



Physical Characteristics	
Fixture Color	White
Length	15.1" dia.
Height	7.6"
Input Cable Length	5ft.
Weight	14.8 lbs

Electrical Characteristics	
Amperage Draw (Input Volts/Amps)	120/1.21 208/0.73 240/0.64 277/0.56
Surge Protection	4kV

Regulatory Qualifications
cULus Listed
DLC Qualified - Model# HW-150C-AB
Lighting Facts Qualified

# Accessories RF13912 - ACRYLIC REFLECTOR FOR 150W/200W HIGHBAY RF13388 - ALUMINUM SHIELD FOR 150W/200W HIGHBAY, SILVER LN13632 - 120 DEGREE PLASTIC FLAT LENS FOR 150W/200W HIGHBAY LN28431 - 50 DEGREE LENS FOR 150W/200W MODERN HIGHBAY



#### Description

Venture Lighting's Modern Highbay luminaires are low profile, durable, and designed for long life and low maintenance. They are designed to quickly and easily upgrade existing H.I.D and fluorescent fixtures.

#### Construction

The high performance LED source is mounted to an aluminum heat sink which is designed to ensure proper thermal management of the system. This design allows for a cooler running LED chip which leads to longer lifetime, better efficacy, and color consistency. Fixtures are rated for an ambient operating temperature range -30°C to 50°C. Modern high bay luminaires are water and dust resistant, with IP65 rating.

#### Optics

The 90W unit comes with a standard 120 degree beam spread for lower mounting heights, but can be adjusted in the field using the 90 degree or 50 degree accessory lens. The 150W and 200W units are equipped with a 90 degree beam spread for higher mounting heights and are also field adjustable with an accessory lens.


### Electrical


The power supply has a range of 120-277V, 50/60 Hz. 0-10V DC dimming capability is standard. The luminaire is rated for damp and dry locations.






# Venture 150W LED Highbay Fixture











(800) 451-2606 Fax: (800) 451-2605 2451 Enterprise Parkway East Twinsburg, Ohio 44087 USA E-mail: venture@adlt.com VentureLighting.com

