

LED Flood Light

PART NUMBER: LF-60WW (WARM WHITE)

LF-60CW (COOL WHITE)



PRODUCT DESCRIPTION:

LED floodlight series 60w. Adopting Bridgelux LED chip as its light source . With its high lighting efficiency but low light decay, it can be used for a long time.

TECHNICAL SPECIFICATIONS:

LED Consumption 60W

Power/Quantity 1pc*60W

Power Consumption 56W

LED Initial Flux 4800 - 5000lm

Luminous efficiency: 76.0lm/w

Color Temperature Warm White:3500K,

Cool White:5000K

Dimension: 11.34in(L) x 14.17in(H) x 4.45in(W)

FEATURES:

1. Stainless Hex socket. The lights can only be opened with specific tool, that is to say, only the professional person can open it, which makes the safety of the products.
2. Silicon rubber instead of glue at every joint to prevent water coming into the internal part.
3. Waterproof VDE 3C rubber cable instead of PVC cable. Low oxidation.
4. Drivers' PF is more than 0.95.
5. Bridgelux LED. High light efficiency (110-120lm/w), high CRI (Ra>70), and low light degradation.
6. Tempered glass.
7. Reflector. Mirror reflection cover can enhance the light reflection.
8. Environmental package. PE bag and EPE package instead of EPS.
9. Baking instead of spray painting.