

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

Our integrated ceiling light strip offers industrial, commercial-grade LED lighting in 4-foot and 8-foot standard lengths. Design can be customized, color can be changed and the canopy can be power-coated to your desired finish of red, black or orange. This corrosion-resistant product's built with formed and welded 22-gauge steel. The light strip includes a snap-in, glare-free frosted lens.

FEATURES

Construction: Die-formed and welded 22-gauge cold rolled steel

Lens: Glare-free snap-in frosted acrylic for even distribution

Voltage: 120-277V


CRI: 83

Dimming: 0-10V, ELV

Life: 50,000 Hours

Warranty: 5 Years carefree for parts & components (labor not included)

Listings: cETLus Listed, IC-rated for damp and dry locations, Assembled in the US



ORDERING INFORMATION Example: (11108-2-D14-30K-010-WH-LV-EM)

Model	Wattage Lumens	Color Temp	Dimming Driver	Finish	Controls	Options
11108	2 Foot	30K 3000K	010 Standard 120-277V 5-Wire 0-10V (100%-10%)	Standard	Optional	EM Remote Emergency Backup Battery
	2-D14 14 watts 1400 lumens					
	2-D20 20 watts 2000 lumens	35K 3500K	ELV 120V 3-Wire Electronic Low Voltage (100%-1%)	BK Black	LV Lutron VIVE™ Wireless	OS Occupancy Sensor w/ Daylight Harvesting
	4 Foot					
	4-D28 28 watts 2800 lumens	40K 4000K		SL Silver	LE Lutron EcoSystem™	VS Vacancy Sensor
	4-D40 40 watts 4000 lumens					
	8 Foot	50K 5000K		Premium ¹	BM Bluetooth Mesh	
	8-D56 56 watts 5600 lumens					
	8-D80 80 watts 8000 lumens					
					RD Red	
				BL Blue		
				GR Green		
				OR Orange		
				SB Satin Brass		

¹ Additional Lead Time will be Applied