

Project Name:

Type:

Quantity:

SHOP NOW

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Alcon Lighting Watson Architectural LED Modern Linear Wall Mount Direct/Indirect Light Fixture** delivers continuous clean lines and clear wall light to commercial, hospitality and residential interior wall lighting applications. Our slim profiles and stylish modern wall sconces offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

AVAILABLE LENGTHS

2FT | W 7.25" x L 24" x H 3" **4FT | W** 7.25" x L 48" x H 3" **8FT | W** 7.25" x L 96" x H 3" **Custom Length |** Consult Factory

FEATURES

Construction: Die-formed and welded 20-gauge cold rolled steel Lens: Semi-specular aluminum louvers Voltage: 120-277V Dimming: 0-10V Life: 60,000 hours Warranty: 5 years carefree for parts & components (Labor not included) Listings: Dry and damp location suitable ARRA complaint



ORDERING INFORMATION Example: (11112-2-D14-30K-010-WH-LV-EM)

Model	Wattage Lumens	Color Temp		Finish -		Options -	
11112-2	D22	27K ²	2700K	MW		OS	Occupancy
24" Surface	22 Watts 1964 Lumens	30K	3000K	LG	Light Gray		Sensor
I	D30	35K	3500K			DL	Damp Location
	30 Watts 2678 Lumens	40K 50K	4000K 5000K			EM7	Emergency Ballast 7 Watts 625 Lumens
						EM10	Emergency Ballast 10 Watts 893 Lumens
11112-4	D40						
48" Surface	40 Watts 3571 Lumens						
	D60						
	60 Watts 5357 Lumens						
11112-8 ¹	D80						
96" Surface	80 Watts 7143 Lumens						
	D120						
	120 Watts 10714 Lumens						
							1 8FT fixtures consist of two 48" fixtures2 Only compatible with 90+ CRI option



