

Project Name:

Type:

Quantity:

## FIXTURE SPECIFICATIONS

### INTENDED USE

The specification grade **Alcon Lighting Sherlock Architectural LED Modern Linear Wall Mount Direct/Indirect Light Fixture** delivers continuous clean lines and clear wall light to commercial, hospitality and residential interior wall lighting applications. Our slim profiles and stylish modern wall sconces offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

### AVAILABLE LENGTHS

**2FT** | W 7.25" x L 24" x H 3"

**3FT** | W 7.25" x L 36" x H 3"

**4FT** | W 7.25" x L 48" x H 3"

**Custom Length** | Consult Factory

### FEATURES

**Construction:** Die-formed and welded 22-gauge cold rolled steel

**Voltage:** 120-277V

**CRI:** 80+ is standard, 90+ for 2700K


**Mounting:** Individual fixture installation or continuous row mounting available (2', 3' and 4' sections can be joined to create longer length fixtures)

**Dimming:** 0-10V

**Life:** 60,000 hours

**Warranty:** 5 years carefree for parts & components (Labor not included)

**Listings:** Dry and damp location suitable, ARRA Compliant



## ORDERING INFORMATION Example: (11113-2-D22-27K-MW-EM7)

Model	Wattage   Lumens	Color Temp	Finish	Options
11113-2 24" Wall	<b>D22</b> 22 Watts   2060 Lumens	<b>27K<sup>1</sup></b> 2700K <b>30K</b> 3000K	<b>MW</b> Matte White <small>Standard</small> <b>SL</b> Silver	<b>OS</b> Occupancy Sensor
	<b>D30</b> 30 Watts   2810 Lumens	<b>35K</b> 3500K <b>40K</b> 4000K <b>50K</b> 5000K		<b>DL</b> Damp Location
		<b>D33</b> 30 Watts   2810 Lumens		<b>EM8</b> 8W Emergency Back-up Battery (1296 Lumen)
				<b>D45</b> 45 Watts   4215 Lumens
11113-3 36" Wall	<b>D40</b> 40 Watts   3747 Lumens <b>D60</b> 60 Watts   5620 Lumens			<b>EM20<sup>2</sup></b> 20W Emergency Back-up Battery (3240 Lumen)
				<b>EM25<sup>2</sup></b> 25W Emergency Back-up Battery (4050 Lumen)
11113-4 48" Wall				

<sup>1</sup> Only compatible with 90+ CRI option  
<sup>2</sup> Not compatible with 24" Model