

SPECIFICATION SHEET

Shop Now

Project Name:	Type:	Ouantity:

INTENDED USE

The specification grade Alcon Lighting 11145 architectural outdoor LED full cut-off wall pack is a high performance fixture offering both durability and style. Made of die-cast aluminum, the 11145 modern LED is wet-location suitable and is the ideal solution for LED wall pack light applications. Use on factories, warehouses, self storage, commercial buildings, entrances and walkways. Featuring field adjustable wattage & lumen with the ability to switch from 25W (3250L), 50W (6500L), 75W (9750L) & 100W (13000L).

FEATURES

Construction: High grade, heavy-duty die cast aluminum Lens: UV and impact-resistant polycarbonate CRI: 70 Wattage & Lumen: Field Adjustable Wattage (Lumen). Capable of switching from 25W(3250L) to 100W(13000L).

Color Temperature Switch: Field Adjustable Color Temperature switching. From 3000K, 4000K & 5000K.

Voltage: 120-277V

Dimming: 0-10V Dimmable

Beam Angle: 100° Life: 50.000 hour

Operating Temperature: -22°F to 113°F


Power Factor: > 0.9

Listings: cULus, IP65, Wet-location Suitable, DLC Premium, FCC listed, RoHS compliant, Meets LM-79 LM-80 Standards.

Warranty: 5 years carefree for parts & components

(labor not included)







ORDERING INFORMATION Example: (13306-27-BK-SP-120)

Model	Finish		Options	
11145	DB Da	rk Bronze ^{Standard}	EM4	4W Emergency Back-Up Battery
	WH	White	EM5	5W Emergency Back-Up Battery
	BK	Black	PS	Dusk to Dawn Photocell Sensor
	SL			

	Wattage & Lumen Switching		
25W	3250L		
50W	6500L		
75W	9750L		
100W	13000L		









Silver