

Project Name:

SHOP NOW

____ Type: _____ Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The Prisma Architectural LED Shallow Shroud and Flat Panel Box is designed to easily convert any flat panel into an aesthetically pleasing ceiling mounted fixture. The Prisma is ideal for commercial lighting applications, including office lighting, retail lighting, as well as modern residential lighting.

AVAILABLE SIZES

1x4 Shallow Shroud - W 12" x L 48" x H 3" 2x2 Shallow Shroud - W 23.95" x L 23.95" x H 3" 2x4 Shallow Shroud - W 23.95" x L 47.65" x H 3"

1x4 Flat Panel - W 11.78 x L 47.25 x H .5" 2x2 Flat Panel - W 23.625 x L 23.625 x H .5" 2x4 Flat Panel - W 23.625 x L 47.25 x H .5"

FEATURES

Construction: Specially designed shallow shroud and flat panel combined Sealed Non-IC type high-grade aluminum Mounting: Surface Light: UV/IR Free Lens: Diffused Frosted Voltage: 120-277V (50/60 Hz) Constant Current Dimming: 5-Wire 0-10V CRI: 80+ Power Factor: >99 Life: L70 - 50,000 Hours Driver: Class 2 Compliant Listings: cULus Listed Warranty: 5 Years Carefree for Parts & Components (Labor Not Included)





ORDERING INFORMATION Example: (11150-14-30K-WH)

1		1		1
Model	Size Wattage Lumens	Color Temperature	Finish	Options
11150	14	35K	wн	EM
	1x4 40 Watts 5000 lms	3500K	White	Emergency
	22	40K	BK	Backup Batter
	2x2 40 Watts 5000 lms	4000K	Black	
	24	50K	SL	
	2x4 60 Watts 6250 lms	5000K	Silver	



FIXTURE DIMENSIONS 4.718 4.688 Ţ, വ Ē ſ 23.750 11.780 4 11.780 47.650 1x4 2x2 **1** 4.688 Ę G 23.750 47.688 23.750

2x4