

Type:

Quantity:

## FIXTURE SPECIFICATIONS

### INTENDED USE

Built with a Black aluminum housing, our 2x2 LED recessed fixture features sound absorbing acoustic felt ideal for spaces that will benefit from reduced noise. The 11166 can be ordered in a variety of ways: as a non-lit, acoustic felt only product that drops from the ceiling, a LED lit product with acoustic felts that is recessed into the ceiling, an a LED only product. This product can be customized in a number of ways to suit open offices, lobbies and reception areas and corridors, and other commercial interiors.

### PRODUCT FAMILY

**11166:** Non-Lit Sound Absorbing Acoustics Fixture

**11166-P:** LED Pendant with Sound Absorbing Acoustics

**11166-R:** LED Regressed Flat Panel with Sound Absorbing Acoustics

### FEATURES

**Wattage & Color Temperature Switch:** Features Field adjustable Wattage and Color temp switch capable of switching wattages from 25 to 40 Watts and color temperatures of 35K to 50K.

**Lens:** Frosted acrylic diffuser

**Voltage:** 120-277V

**Life:** 50,000 Hours

**Warranty:** 5 Years carefree for parts & components (labor not included)

**Listings:** cULus, DLC, ARRA compliant, BAA compliant



LED	Watts	Color Temp	Lumen Output
Wattage & Color Temperature Selectable	40W	3500K	3828lm
		4000K	3828lm
		5000K	3897lm
	30W	3500K	2949lm
		4000K	2975lm
		5000K	3001lm
	25W	3500K	2523lm
		4000K	2544lm
		5000K	2566lm



## ORDERING INFORMATION Example: (11166-AD-2-RT-010)

Model	Size	Mounting	Dimming	Options
<b>11166-AD</b>	<b>1</b> 1" Acrylic Drop	<b>RT</b> Recessed T-bar	<b>010</b> <small>Standard</small> 0-10V Dimming (120-277V)	<b>OS</b> Bi-Level Occupancy Sensor
	<b>2</b> 2" Acrylic Drop	<b>FK</b> Flange Kit for Hard Ceiling	<b>ELV</b> ELV Dimming (120-277V)	<b>EM8</b> 8W Emergency Back-Up Battery
	<b>4</b> 4" Acrylic Drop		<b>TRIAC</b> TRIAC Dimming (120V Only)	<b>EM16</b> 16W Emergency Back-Up Battery
	<b>6</b> 6" Acrylic Drop			<b>EM20</b> 20W Emergency Back-Up Battery