

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

Tubular LED lighting is ideal for illuminating warehouses, commercial kitchens, gyms and other middle to high ceiling places with a wet-location IP67 rating. Surface or aircraft cable pendant mounted downlighting (in white with variable options for lumens output) lights the space with vapor-tight construction.

DIMENSIONS

4 Foot | **L** 49.625" x **W** 3.875" x **H** 3.375"

8 Foot | **L** 95.375" x **W** 3.875" x **H** 3.375"

FEATURES

Construction: Aluminum housing with polycarbonate lens

Mounting: Surface mount and 118" aircraft cable pendant mount kit included

CRI: 80+

Input Voltage: 120/277V, 50/60Hz

Dimming: 0-10V Dimming

Ambient Operating Temperature: 22°F to 131 °F (-30°C to 55°C)

Color Temperature: 5000K Day light

LED Life: 129,000 Hours

Listings: UL, DLC Premium, IP67, IP69K, NSF

Warranty: 5 years carefree for parts & components (labor not included)



4' & 8'

Alcon 11176 Linear Wet-Location LED Tube Light

ORDERING INFORMATION Example: (11176-4-34)

Model	Length Wattage Lumens
11176	4-34
	4 FT 34 Watts 4525 lum
	4-58
	4 FT 58 Watts 7766 lum
	4-80
	4 FT 80 Watts 10808 lum
	8-100
	8 FT 100 Watts 13340 lum

COMPATIBLE DIMMERS

Manufacturer	Dimmer SKUs
	DVSTV
	DS710-10Z
	DF10P-C1
	SF10P-W
	0A019

