

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE



This architectural cylinder wall light is a versatile low-glare lighting fixture. This product can be used indoors and outdoors for commercial or retail purposes. The downlight can also be used to accent and create dramatic effects or provide safety and security. This fixture is exclusively designed for downlighting.

PRODUCT FAMILY

- 11218-DIR** Cylinder Direct
- 11218-ADJ** Cylinder Adjustable
- 11219-2D** Cylinder Direct Indirect
- 11220-DIR** Square Direct
- 11221-2D** Square Direct Indirect

FEATURES

- Construction:** Round One Piece High Grade Aluminum with corrosion-resistant finish
- Light Engine:** LED Chip-On-Board
- Lens:** Tempered Glass and Silicone O-Ring
- Reflector:** Glare-Free, One piece, Heavy Gauge Aluminum
- Mounting:** Includes Bracket for Installation Directly to a 4" octagonal electrical junction-box
- Voltage:** 120V (Non-Dimming), 120V/277V (Dimming)
- CRI:** 84+
- Dimming:** Universal Dimming System Compatible with 2-Wire TRIAC, 3-Wire ELV, and 5-Wire 0-10V Dimmers
- Life:** L70 - 50,000 Hours
- Emergency:** 90 Minutes Minimum, Remote Test Switch, Plate Cover, Junction Box Included
- Listing:** ETL/cETL Listed Suitable for Wet Location. Assembled in the US (IP65)
- Electrical:** Electronic Direct Current Class 2 driver
- Warranty:** 5 Years Carefree for Parts and Components (Labor not included). We recommend the use of surge protectors on the power entering LED Housings. Surge damage is not covered by warranty.
- Compliance:** Dark Sky Compliant when fixture is pointing downward.



ORDERING INFORMATION Example: (11218-DIR-L15-B60-UNI-40K-WH-EM)

Model	Lumen	Beam Spread	Dimming	Color Temperature	Finish	Options
11218-DIR Pavo-Cylinder	L10 1000 lm (10W) <i>Standard</i>	B2 2° Narrow Spot	ND <i>Standard</i>	27K 2700K	WH White	EM Emergency
	L15 1500 lm (15W)	B10 10° Spot	Non-Dimming (120V)	30K 3000K	BK Black	
	L22 2200 lm (22W)	B20 20° Wide Spot	UNI	35K 3500K	SL Silver	
	L26 2600 lm (30W)	B45 45° Flood	Universal (120V / 277V)	40K 4000K <i>Standard</i>	BZ Bronze	
		B60 60° Wide Flood <i>Standard</i>		50K 5000K		
		WW Wall Wash				
	IV Type IV (forward throw)					

Pavo Architectural LED 6-Inch Cylinder Wall Downlight

COLOR TEMPERATURE GUIDE

