

FEATURES & SPECIFICATIONS

INTENDED USE

The **Pavo Turtle Friendly Architectural LED Surface Ceiling Mount Down Light** is a versatile low glare lighting fixture that can be used indoor and outdoor, up or down, in commercial or retail settings. The Pavo LED Architectural Surface Mount Down Light is used to accent and create dramatic effects while providing a great source of lighting from above.

DETAILS

W 5.9" x **H** 4.75"

Construction: Square one piece high grade aluminum extrusion, die cast aluminum top plate
Tamper Resistant

Light Engine: LED Chip-On-Board

Lens: Round one piece extruded aluminum with powder coat finish, clear tempered glass, and silicone o-ring

Reflector: Glare-free, one piece, heavy gauge aluminum

Mounting: Includes bracket for installation directly to a 4" octagonal electrical junction-box

ADDITIONAL FEATURES

Voltage: 120 (120-277 Available for Dimming)

Wattage: 15W

Color Temperature: 590nm Amber



CRI: 84+

Dimming: Universal dimming system that works with most 3-Wire ELV, 2-Wire Incandescent and 5-Wire 0-10V fluorescent dimmers

Life: L70 - 50,000 Hours

Emergency: 90 minutes minimum

Remote test switch, plate cover, junction box included



5 15/16"

Turtle Safe Requirements:

Low: The product is designed for low to medium ceiling heights and delivered lumen output is sufficient to produce enough footcandles to satisfy building codes but not overpower the environment with excessive lumen output.

Shielded: The trim is deeply recessed and provides a minimum of 50° of glare cutoff. The trim reflector color is black to limit reflections.

The beam spread is tightly controlled.

Long: LED color is verified as 585nm minimum and 595nm maximum.

Ordering Information:

Example: (11224-TF-DUN-WH-EM)

Model	Beam Spread	Dimming	Finish	Options
<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>	<input type="text"/>
11224-TF Pavo	(Blank) 60° Wide Flood P 2° Pencil NS 10° Narrow Spot S 20° Spot F 45° Flood	(Blank) Non-Dimming (120V) DUN UniDim (120/277V)	WH White BK Black BR ¹ Bronze SL ¹ Silver	EM Remote Emergency Backup Battery HL Hexcell Louver ¹ DS Daylight Sensor ¹

¹Special Order. Minimum lead time may apply.