SPECIFICATION SHEET

Project Name: Type: Quantity:

INTENDED USE

This wall-mounted, cylindrical LED light is made for safety in wet exterior locations. Get durable uplighting and downlighting in commercial space such as outdoor dining and/or a campus or residential exterior.

FEATURES

Construction: 6061 marine grade corrosion

resistant aluminum

Mounting: Mounts on a standard size J-Box

Wattage: 2x23 Watts Lumens: 4116 Lumen Total

CRI: 90+


Input Voltage: 120/277V, 50-60Hz

Dimming: TRIAC and ELV LED Life: 50,000 hours

Listings: cULus for Wet Location, Energy Star,

Made in America

Warranty: 4 years carefree for parts & components (labor not included)

















ORDERING INFORMATION Example: 11234-24-27K-BK

Model	Height	Color Temp	Finish	Options
11234	24 24 Inch36 36 Inch	27K 2700K 30K 3000K 35K 3500K 40K 4000K	BK Black WH White BR Bronze GR Gray SB Satin Brass Satin SA Aluminum Antique AB Brass	XEM Emergency Battery (External)



COMPATIBLE DIMMERS FOR STATIC WHITE

Manufacturer	Model	Туре
Leviton	ILLUMATECH IPL06	LEADING EDGE
Lutron	NOVA T NTLV-600	LEADING EDGE
Lutron	SKYLARK S-600	LEADING EDGE
Leviton	IG4005 6631	LEADING EDGE
Lutron	LUMEA LG-600P	LEADING EDGE
Leviton	VPE06	TRAILING EDGE
Lutron	SELV-303P	TRAILING EDGE

