



## FEATURES & SPECIFICATIONS

### INTENDED USE

The **Alcon Lighting Tesla Dual Gimbal Spot Light Architectural LED Suspension Lighting** features easy installation and clean, uniform, and efficient lighting with adjustable Spot Light additions. The Tesla Dual LED Suspension Lighting is perfect for indoor and outdoor commercial and institutional interior spaces with no UV emittance.

### DETAILS

**W** 4.375" x **H** 4.625"

**Construction:** Extruded Aluminum

65% Recycled Materials

**Electronic Driver:** Over voltage, over current, over temperature, and short circuit protection

EMI & RFI meets FCC part 15 (Class A) Auto Recovery

**Optics:** High performance frosted lens and filter Premium binned LEDs

True Color & Lumen Consistency

**Spot Light Interior Positioning:** 0°-35°

**Mounting:** 50" Power feed canopy kit included

**Weight:** 2.5 lbs per foot

### ADDITIONAL FEATURES

**Voltage:** 120-277 & 347

**Dimming:** 0-10V

**CRI:** 85

**Life:** L70 - 80,000 Hours

**Beam Angle:** 90° Horizontal x 85° Vertical


**Power Factor:** >.95

**THD:** max <20%

**Spot Lights:** 7W, 500 lumens, Non-Dimmable

**Listings:** ETL Listed to UL Standards for dry or damp locations

Fixture suitable for wet location under canopy/covered ceilings with "WL" option



### Ordering Information:

Example: (12000-2-G-4F-10D-WH-G10-EM-30K-DM)

Model	Length	Wattage/Ft	Finish	Spot Light <sup>1</sup>	Options	Color Temp
<b>12000-2-G</b> Tesla Dual - Gimbal	<b>4F</b> 4' <b>8F</b> 8' <b>XXF</b> Total Run	<b>10D</b> Down Light 10 watts, 700 lms <b>15D</b> Down Light 15 watts, 990 lms <b>10DI</b> Down Light 10 watts, 700 lms Up Light 15 watts, 990 lms <b>15DI</b> Down Light 15 watts, 990 lms Up Light 10 watts, 990 lms	<b>WH</b> White (Standard) <b>BK</b> Black <b>SL</b> Silver <b>XXXX</b> Custom RAL# <b>PW</b> Premium Wood Grain	<b>G10</b> 10° Spot <b>G20</b> 20° Medium Flood <b>G36</b> 36° Flood	<b>DS<sup>1</sup></b> Daylight Sensor <b>OS<sup>1</sup></b> Occupancy Sensor <b>WL</b> Wet Location <b>EM</b> Emergency Backup (1400 lms)	<b>30K</b> 3000K <b>35K</b> 3500K <b>40K</b> 4000K
<b>Driver</b>						
<b>DM</b>	120/277V 0-10V Dimming					
<b>DM-347</b>	347V 0-10V Dimming					

<sup>1</sup>Add 4.5" to Channel per Option  
(2 Spot Lights per Fixture, 1 Spot Light on Each End)  
<sup>2</sup>Recommended for Low Ceilings Only

Alcon Lighting 12000-2-G Tesla Dual Gimbal Spot Light Architectural LED Linear Suspension Lighting Pendant Mount Direct/Indirect Fixture