



FEATURES & SPECIFICATIONS

INTENDED USE

The **Alcon Lighting Tesla Quadro Spot Light Architectural LED Suspension Lighting** features easy installation and clean, uniform, and efficient lighting with adjustable Spot Light additions. The Tesla Quadro LED Suspension Lighting is perfect for indoor and outdoor commercial and institutional interior spaces with no UV emittance.

DETAILS

W 4.375" x **H** 4.625"

Construction: Extruded Aluminum
65% Recycled Materials

Electronic Driver: Over voltage, over current, over temperature, and short circuit protection

EMI & RFI meets FCC part 15 (Class A) Auto Recovery

Optics: High performance frosted lens and filter Premium binned LEDs

True Color & Lumen Consistency

Mounting: 50" Power feed canopy kit included

Weight: 2.5 lbs per foot

ADDITIONAL FEATURES

Voltage: 120-277 & 347

Dimming: 0-10V

CRI: 85

Life: L70 - 80,000 Hours

Beam Angle: 90° Horizontal x 85° Vertical

Power Factor: >.95

THD: max <20%

Spot Lights: 7W, 500 lumens, Non-Dimmable

Listings: ETL Listed to UL Standards for dry or damp locations

Fixture suitable for wet location under canopy/covered ceilings with "WL" option



SHOP NOW >



Spot Light (Outer)

Spot Light (Inner)




Accent 2" Square
0°-20° Positioning



Pull Down 2" Round
0°-85° Positioning



Gimbal 2" Round
0°-35° Positioning



Ordering Information:

Example: (12000-4-4F-10D-WH-A10-P10-A10-EM-30K-DM)

Model	Length	Wattage/Ft	Finish	Inner Spot Light ¹	Outer Spot Light ¹	Options
12000-4	4F 4'	10D Down Light 10 watts, 700 lms	WH White (Standard)	<i>Accent</i>	<i>Accent</i>	DIBW² Direct with Indirect Batwing Technology
Tesla	8F 8'	15D Down Light 15 watts, 990 lms	BK Black	A10 10° Spot	A10 10° Spot	DS¹ Daylight Sensor
Quadro	XXF Total Run	10DI Down Light 10 watts, 700 lms Up Light 15 watts, 990 lms	SL Silver	A20 20° Medium Flood	A20 20° Medium Flood	OS¹ Occupancy Sensor
		15DI Down Light 15 watts, 990 lms Up Light 10 watts, 990 lms	XXXX Custom RAL#	<i>Pull Down</i>	<i>Pull Down</i>	WL Wet Location
			PW Premium Wood Grain	P10 10° Spot	P10 10° Spot	EM Emergency Backup (1400 lms)
				P20 20° Medium Flood	P20 20° Medium Flood	
				P36 36° Flood	P36 36° Flood	
				<i>Gimbal</i>	<i>Gimbal</i>	
				G10 10° Spot	G10 10° Spot	
				G20 20° Medium Flood	G20 20° Medium Flood	
				G36 36° Flood	G36 36° Flood	

¹Add 4.5" to Channel per Option
(4 Spot Lights per Fixture, 2 Spot Light on Each End)
²Recommended for Low Ceilings Only

Alcon Lighting 12000-4 Tesla Quadro Architectural LED Linear Suspension Lighting Pendant Mount Direct/Indirect Fixture