

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

The integrated color-changing LED lightstrip has a 1-inch lens aperture width and is available in standard lengths of 2-foot, 4-foot, 6-foot, 8-foot and custom cuts. Our commercial-grade product with dimmable light via Android or iOS application or optional controls can be joined in seamless runs of any length. This 24-voltage lightstrip offers direct downlight secured in a military-grade, field-cutttable aluminum channel.

PRODUCT FAMILY

- 12100-10-P** | Pendant
- 12100-10-S** | Surface
- 12100-10-R** | Recessed
- 12100-10-LR** | Low-Profile Recessed
- 12100-10-PR** | Perimeter Recessed
- 12100-10-PR-RGBW** | Perimeter Recessed RGBW

FEATURES

- Construction:** Durable military grade aluminum, field cuttable can be installed in any drywall thickness
- LED Driver:** Remote non-dimming transformer is provided home run required at every 16'
- Beam Angle:** 120°
- Lens:** Glare-free snap-in frosted acrylic for even distribution
- Shape Design:** Fixture profile can be miter cut—in the field—to achieve desired shape design
- Finish:** Matte White
- Voltage:** 24V DC Constant Voltage
- Lumens:** 547 Lm/Ft. (167 Lm. (RGB) | 380 Lm. (White))
- Wattage:** 8.8W per foot
- CRI:** 90+
- Dimming:** Light is Dimmable via iOS/Android Application or Optional Controls
- WiFi Controls (iOS/Android):**
Mobile App: Easy Home Smart Home
DMX Wall App: WiFi 104
- Life:** 50,000 Hours
- Warranty:** 5 Years Carefree for Parts & Components (Labor Not Included)
- Listings:** cUL Listed, Title 24 Certified, Dry Location IP45 (LED Component Only), Optional Wet Location IP65 (LED Component Only)



ORDERING INFORMATION Example: 12100-10-R-RGBW-2-RGBW27K-RTL-RF

Model	Length	Color Temp	Mount Type	Flange Finish ¹	Controls	DMX Decoder	Options
12100-10-R-RGBW Recessed RGBW	2 2 Foot	RGBW27K RGB + 2700K	RTL Trimless	WH White	WiFi Mobile Application + WiFi	(Blank) None required	WL² Wet Location
	4 4 Foot	RGBW30K RGB + 3000K	RT T-Bar	BK Black	RF RF Remote Control (White)	DEC-4C 4-Channel RJ45	IP65
	6 6 Foot	RGBW40K RGB + 4000K	RF Flanged	SL Silver	DMX DMX Wall Control (White)	DEC-5C 5-Channel RJ45/XLR	
	8 8 Foot	RGBW50K RGB + 5000K			DMX-WIFI-W DMX Wall Control (White) + WiFi		
	XX Custom Length <small>Replace XX with Length in Feet</small>				DMX-WIFI-B DMX Wall Control (Black) + WiFi		

¹ Not required for Trimless

² Wet location option is available for the LED component only

COLOR TEMPERATURE

COLOR TEMPERATURE GUIDE



<p>2700K WARM WHITE</p> <p>friendly personal intimate</p> <p>HOMES LIBRARIES RESTAURANTS</p> <p>✓</p>	<p>3000K SOFT WHITE GLOW</p> <p>soft warm pleasing</p> <p>HOMES HOTEL ROOMS LOBBIES RETAIL STORES</p> <p>✓</p>	<p>3500K NEUTRAL GLOW</p> <p>sociable inviting non-threatening</p> <p>EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS</p> <p>✗</p>	<p>4000K DAYLIGHT GLOW</p> <p>neat clean efficient</p> <p>OFFICES CLASSROOMS MASS MERCHANDISERS SHOWROOMS</p> <p>✓</p>	<p>5000K CRYSTAL WHITE GLOW</p> <p>bright cool alert</p> <p>GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS</p> <p>✓</p>
--	---	--	---	---