

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Continuum 2" Architectural Direct and Indirect LED Linear Wall Mount Lighting** delivers continuous clean lines and clear light to commercial, hospitality and residential interior wall lighting applications. Our modern, slim profiles and stylish linear wall designs offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The Continuum integrated LED linear lighting is available in standard lengths of 2', 3', 4', and 8', and can be joined together in seamless runs of any length.

PRODUCT FAMILY

12100-20-P	Pendant
12100-20-W	Wall Mount
12100-20-S	Surface
12100-20-R	Recessed



AVAILABLE LENGTHS

2FT	W 2.5" x L 24" x H 4"
4FT	W 2.5" x L 48" x H 4"
8FT	W 2.5" x L 96" x H 4"

Continuous Run | Consult Factory

FEATURES

Construction: Die-Formed and Welded 22-Gauge Cold Rolled Steel
Continuous Row: Tandem Mount for Continuous Run Application, Equipped with Male & Female Quick Connect Harnesses
Lens: Glare Free Snap In Frosted Acrylic for Even Distribution
Voltage: 120-277V (347V and 480V Available for Canadian Projects, Consult Factory)
CRI: 80+ (90+ available, Consult Factory)
Universal Dimming: TRIAC (Forward-Phase), ELV (Reverse-Phase), 0-10V
Power Factor: > .95
THD: < 20
Life: 100,000 Hours L70
Operating Temperature: -4°F (-20°C) - 122°F (50°C)
Emergency Lumens: System Lumens x Emergency Wattage / System Wattage
Warranty: 5 Years Carefree for Parts & Components (Labor Not Included), 10 Year Option Available
Listings: CA Title 24 Compliant, cETL Listed, LED Chips Tested to LM-80 Standards, UL Listed for Dry & Damp Location



ORDERING INFORMATION Example: (12100-20-W-24 -D18-U9-30K-WH-8-LV-EM5)

Model	Lumens (Direct Downlight)	Lumens (Indirect Uplight)	Color Temp	Finish	CRI
12100-20-W-24 24" Wall	D13 13 watts 1300 lumens D18 Standard 18 watts 1800 lumens D27 27 watts 2700 lumens	(Blank) No Uplight U9 9 watts 900 lumens	Residential 27K 2700K 30K 3000K Commercial 35K 3500K 40K 4000K Industrial 50K 5000K	WH White Standard BK Black SL Silver RAL Custom Consult Factory	8 Standard 80+ CRI 9 90+ CRI
12100-20-W-48 48" Wall	D27 27 watts 3100 lumens D36 Standard 36 watts 4100 lumens D54 54 watts 6200 lumens	(Blank) No Uplight U18 18 watts 2500 lumens			
12100-20-W-96 96" Wall	D54 54 watts 6200 lumens D72 Standard 72 watts 8200 lumens D108 108 watts 12400 lumens	(Blank) No Uplight U36 36 watts 5000 lumens			
			Controls Optional LV Lutron VIVE™ Wireless LE Lutron EcoSystem™ BM Bluetooth Mesh	Options EM5 5W Emergency Ballast EM8 8W Emergency Ballast EM16 16W Emergency Ballast OS Occupancy Sensor w/ Daylight Harvesting DS Daylight Dimming Photo Sensor ARRA Assembled in USA 10W 10 Years Limited Warranty	

Formerly: 11158 Beam 20