

Project Name: _____ Type: _____ Quantity: _____

INTENDED USE

This linear pendant or surface-mounted LED light delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting. The modern, slim profile comes in standard lengths of 2, 3, 4 and 8-feet but is available for continuous runs of any length. Excellent illumination, exceptional performance and versatility for offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

FEATURES

Construction: Extruded aluminum housing Powder coat finish

Dimming: 1-10V dimming down to 10%

Wattage: Wattage selectable from 10W/7.5W/5W per FT

Color Temperature: CCT adjustable from 3000K, 3500K, 4000K.

Must select color temperature for Micro Reflector optics

Light Distribution: Adjustable via dip switch


Voltage: 110-277

CRI: 80+


Life: 50,000 Hours

Warranty: 5 Years Free of Defects in Materials & Craftsmanship

Listings: cULus listed for damp locations




W 2.34"



Light distribution options via DIP switch

- 100% Uplight
- 100% Downlight
- 50% down, 50% up
- 70% down, 30% up
- 10% down, 90% up
- 30% down, 70% up
- 90% down, 10% up

Lens	Lumen Package		
	High	Medium	Low
Standard Diffuser	1150lm/ft, 10w/ft	860lm/ft, 7.5w/ft	575lm/ft, 5w/ft
Louver	900lm/ft, 10w/ft	675lm/ft, 7.5w/ft	450lm/ft, 5w/ft
Micro Reflector	1150lm/ft, 10w/ft	860lm/ft, 7.5w/ft	575lm/ft, 5w/ft
Regressed	950lm/ft, 10w/ft	710lm/ft, 7.5w/ft	475lm/ft, 5w/ft



ORDERING INFORMATION Example: (12100-22-P-2-D-CTS-W-DJ-5W-R)










Model	Mouting	Length	Optics	Color Temp	Finish	Ceiling Type	Pendant Type	Canopy	Options
12100-22	P Pendant S Surface R Recessed W Wall	2 2 Foot 3 3 Foot 4 4 Foot 8 8 Foot	D Standard Diffuser L Louver R Regressed M Micro Reflector	CTS Color Temperature Switch (30K/35K/40K) <small>Only for Micro Reflector</small> 30K 3000K 35K 3500K 40K 4000K	W White B Black RAL# See Pg. 2 for custom finishes	DJ Standard Dry Wall J-Box Mount D9/15 Drop Ceiling Clips for 9/16" and 15/16" Flat Ceiling D9S Drop Ceiling Clips for 9/16" Slot Ceiling D15 Drop Ceiling Clips for 15/16" Slot Ceiling	(Blank) Not Required 5W Standard 5 ft white power cord + 5ft aircraft cable 5B 5 ft black power cord + 5ft aircraft cable 12W 12 ft white power cord + 12ft aircraft cable 12B 12 ft black power cord + 12ft aircraft cable	R Standard Round S Square	O¹ Occupancy Sensor IEM 8W Internal Emergency Back-up Battery

¹ Only for round canopy








CUSTOM FINISHES



Set up fee and longer lead time will be applied on non-standard finishes.

Metropolitan

	Silver	RAL #9022
	Asher Grey	RAL #7004
	Mason	RAL #7039
	Slate	RAL #7031
	Tech Grey	RAL #7016
	Chocolate Spice	RAL #8017
	Urban Native	RAL #8025
	Carmin	RAL #8028
	Reseda Green	RAL #6011

Vibrant

	Violet Dreams	RAL #4006
	Purple Red	RAL #3004
	Carmine Red	RAL #3002
	Rose	RAL #3017
	Pure Orange	RAL #2004
	Traffic Yellow	RAL #1023
	Daisy	RAL #1018
	Antique Spring	RAL #6019
	Island Skye	RAL #6027
	Sky Blue	RAL #5015



AVAILABLE CANOPIES



1.6" Round
(Non Power Feed)



4.5" Round
(Power Feed)



4.5" Round With
Emergency
Driver
(Non Power Feed)



5.8" Round
With
Occupancy
Sensor
(Power Feed)



1.6" Square
(Non Power Feed)



4.5" Square
(Power Feed)



4.5" Square With
Emergency
Driver
(Non Power Feed)

COLOR TEMPERATURE GUIDE

