

## FIXTURE SPECIFICATIONS

### INTENDED USE

The specification grade **Continuum 40 Architectural Linear LED Wall Mount Lighting** delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish designs offer excellent illumination, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The integrated LED Continuum is available in standard lengths of 2', 4', and 8', and can be joined together in seamless runs of any length.


### PRODUCT FAMILY

- 12100-40-P** | Pendant
- 12100-40-W** | Wall Mount
- 12100-40-S** | Surface
- 12100-40-R** | Recessed



### AVAILABLE LENGTHS

- 2FT** | W 4" x L 24" x H 4"
- 4FT** | W 4" x L 48" x H 4"
- 8FT** | W 4" x L 96" x H 4"

**Continuous Run** | Consult Factory



Wall Mount



### FEATURES

- Construction:** Die-Formed and Welded 22-Gauge Cold Rolled Steel
- Continuous Row:** Full Ability to Tandem Mount for Continuous Run Application, Equipped with Male & Female Quick Connect Harnesses
- Custom Design:** Offered with Pre-Fabricated and Fully Illuminated Corners
- Lens:** Glare Free Snap In Frosted Acrylic for Even Distribution
- Power Factor:** > .95
- THD:** < 20
- Life:** 100,000 Hours L70
- Operating Temperature:** -4°F (-20°C) - 122°F (50°C)
- Emergency Lumens:** System Lumens x Emergency Wattage / System Wattage
- Warranty:** 5 Years Carefree for Parts & Components (Labor Not Included), 10 Year Option Available
- Listings:** CA Title 24 Compliant, cETL Listed, LED Chips Tested to LM-80 Standards, UL Listed for Dry & Damp Location



## ORDERING INFORMATION Example: (12100-40-W-D18-U18-S-4-80-30K-WH-3-D10-LV-EM5)

Model	Lumens (Direct Downlight)	Lumens (Indirect Uplight)	Shape	Size	CRI	Color Temp	Finish
<b>12100-40-W</b> Wall	(Per 4 Foot Sections) <b>D18</b> 18 watts   2700 lumens	(Per 4 Foot Sections) <b>(Blank)</b> No Uplight	<b>S</b> Single Unit	<b>2', 4', or 8'</b>	<b>80</b> Standard <b>90</b>	<b>Residential</b>	<b>WH</b> White <sup>Standard</sup> <b>BK</b> Black <b>SL</b> Silver <b>RAL</b> Custom <small>Consult Factory</small>
	<b>D36</b> 36 watts   4600 lumens	<b>U18</b> 18 watts   2700 lumens				<b>27K</b> 2700K <b>30K</b> 3000K	
	<b>D54</b> 54 watts   6500 lumens	<b>U27</b> 27 watts   3300 lumens	<b>Commercial</b>				
			<b>35K</b> 3500K <b>40K</b> 4000K <b>Industrial</b>				
			<b>CR</b> Continuous Run	<b>Total Run (in Feet)</b> <input type="text"/>		<b>50K</b> 5000K	

### Voltage

- 1** 120 - 277V
- 3** 347V
- 4** 480V

### Dimming Driver

- D10** <sup>Standard</sup>  
0 - 10V (100 - 1%)
- ELV**  
Electronic Low Voltage
- E5** Lutron EcoSystem™  
5-Series 5%
- E1** Lutron EcoSystem™  
Hi-Lume 1%
- S50**  
50%-100% Step
- DALI**  
100% - 5%

### Controls

- Optional**
- LV**  
Lutron VIVE™ Wireless
- LE**  
Lutron EcoSystem™
- BM**  
Bluetooth Mesh

### Options

- EM5** 5W Emergency Ballast
- EM8** 8W Emergency Ballast
- EM16** 16W Emergency Ballast
- OS** Occupancy Sensor w/  
Daylight Harvesting
- DS** Daylight Dimming  
Photo Sensor
- ARRA** Assembled in USA
- 10W** 10 Years Limited Warranty