

FIXTURE SPECIFICATIONS

INTENDED USE

The recessed light with die-formed and welded 22-gauge cold-rolled steel provides architectural-grade linear lighting for today's residential and commercial or hospitality interior space. Our slim modern product emits light with strong performance and versatility in a variety of settings, including offices, classrooms, conference rooms, museums, retail outlets, restaurants and hotels. Featuring a customizable design, this fixture is available in standard lengths of 4' and 8', and can be joined in seamless runs. Glare-free snap-in lens included.

AVAILABLE LENGTHS

4FT | W 1.48" x L 48.4" x H 2.6"

8FT | W 1.48" x L 96.4" x H 2.6"

Continuous Run | Consult Factory

FEATURES

Construction: Die-Formed and Welded 22-Gauge Cold Rolled Steel

Continuous Row: Full ability to tandem mount for a segmented continuous run from 1', 2', 3', 4' and 8' channels.

Lens: Glare Free Snap In Frosted Acrylic for Even Distribution

Wattage: 30 Watts per 4 foot sections

Lumens: 2800 Lumens per 4 foot sections

Voltage: 120-277V

Dimming: 5-Wire 0-10V (100%-10%)


CRI: 80+

Life: 50,000 Hours


Warranty: 1 Year Carefree for Parts & Components

(Labor Not Included)

Listings: cULus, Suitable for Dry and Damp Locations



ORDERING INFORMATION Example: (12100-15-R-4-30K-SA)

Model	Mount Type	Length	Color Temp	Finish ³
12100-15	R Trimless	4 4 Foot Single Unit	30K 3000K	SA Satin Aluminum <small>Standard</small>
	RF ¹ Flange		40K 4000K	WH White
		CR ² Continuous Run		
		Total Run (in Feet)		
				

¹ Flange width is 3.25".

² Can only be done in increments of 4 foot. A home run would be needed every 4FT.

³ Not required for Trimless.