

SHOP NOW >

FIXTURE SPECIFICATIONS

INTENDED USE


The specification grade **Continuum 45 Architectural LED Linear Square Pendant Lighting** delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting applications. Our modern, hanging light fixtures and stylish linear chandelier designs offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

FEATURES

Construction: Die-Formed and Welded 22-Gauge Cold Rolled Steel 1/2" Regressed Bottom Flange for Uniformity and Rigidity Custom Design: Offered with Pre-Fabricated and Fully Illuminated Corners Lens: Glare Free Snap In Frosted Acrylic for Even Distribution Voltage: 120-277V (50/60 Hz) Constant Current Dimming: 5-Wire 0-10V, 3-Wire ELV, 3-Wire Lutron L3D Life: 50,000 Hours L70 CRI: 80+ / 90

Warranty: 5 Years Carefree for Parts & Components (Labor Not Included) **Listings:** CA Title 24 Compliant, cETL Listed, LED Chips Tested to LM-80 Standards





ORDERING INFORMATION Example: (12100-P-45-D/I-R24-SQ-4x4-30K-DM10-AC48-WH-WH-SEM)

Model	Size	Distribution	Lumen Output	Shape		X			
- 12100-P	45 4" x 5"	D/I Direct/Indirect	(Per 4 Foot Sections) R24 UP: 12 watts DOWN: 24 watts 3600 lms	Square	Width				
			R36 UP: 18 watts DOWN: 36 watts 5400 lms	- RC Rectangle	Width	IGTH X Lengti			
Color Temp	o [Driver	Mounting	Finish		Powe	er Cord	Options	
Residential 27K 2700H 30K 3000H Commercial 35K 3500H	K 5 K 0 (1 K 3	- DM10Standard -Wire -10V Dimming 100%-D0%) ELV -Wire lectronic Low	AC48 ² 48" Adjustable Aircraft Cable (x2) AC144 ² 144" Adjustable Aircraft Cable (x2) ST24 ² 24" Stem (x2)	- WH ^{Standard} White BK Black SL Silver SB	Blue OR Orange GR Green RD	WH BK	White Black	- SEM Single Side Intern Emergency Pack (10W 1000 lms) DEM Dual Side Internal Emergency Pack	
40K 4000k	κ ν (1 Κ <u>Ι</u> L	voltage (Jouge-196) -Wire L3D utron Hi-lume (00%-196)	STXX ² Custom Stem Length ³	Satin Brass	Red RAL Consult Factory			(20W 2000 lms)	¹ 90 CRI ² 0.4" Thick 5-Conductor Power Cable (x1) 5" Round Canopy (x2)

Alcon Lighting 12100-P-45 Continuum 45 Architectural LED Square/Rectangle Pendant Mount Direct/Indirect Light Fixture

