



FEATURES & SPECIFICATIONS

INTENDED USE

The Alcon Lighting 12146 Capsule Architectural **LED Pendant Mount Direct/Indirect Luminaire**

features soft and diffused lighting that ensures maximum visual comfort and balanced shadows. The Capsule is ideal for indoor applications in residential, commercial, institutional, or architectural installations.

DETAILS

4 FT - W 9" x L 48" x Depth 3" **Construction:** Extruded Aluminum Die cast aluminum flat end caps

Finish: Matte White

Lens: White Acrylic Diffuser

4' fixture sections for nominal suspension spacing of

4'

4' sections can be joined to form longer length

fixtures

(Hardware for Continuous Row Mount Included)

ADDITIONAL FEATURES

Voltage: 120-277 (50/60 Hz)

Lumens:

	Down Only	90%/10%	50%/50%
36W	3960	2633/264	2539/2289
54W	5940	4111/413	3582/3230
81W	8910	6329/635	5144/4640

Dimming: 0-10V 1~100%

CRI: 85+

Power Factor: +0.9

Operating Temperature: -20°C (-4°F) - 50°C (122°F)

Life: L70 - 50,000 Hours



















Ordering Information:

Example: (12146-36W-100-30K-AC48-T-EM5)

Model	Wat	ttage	je Distribution		Color Temp		Mounting		Ce	eiling	Options	
12146	36W	36 watts	100	100% Direct Only	30K	3000K	AC48	48" Adjustable Aircraft Cable	T	T-Bar	EM5	5W Emergency
	54W	54 watts		90% Direct/ 10% Indirect 50% Direct/ 50% Indirect	35K	3500K 4000K 5000K	AC96	96" Adjustable Aircraft Cable 24" Stem Mount Kit	Н	Hard	EM8	Ballast 8W Emergency
	81W	81 watts	9010		40K							Ballast
			5050		50K 500		ST24			EM16	16W Emergency Ballast	
							ST48	48" Stem Mount Kit			BSC	Straight Connector