

## FIXTURE SPECIFICATIONS

### INTENDED USE




The specification grade **Alcon Lighting i66 Series Architectural LED Linear Suspended Pendant Mount Direct Light Fixture** delivers continuous clean lines and clear light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish linear chandelier designs offer excellent direct down lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

### AVAILABLE LENGTHS

- 2FT** | W 6" x L 24" x H 6"
- 4FT** | W 6" x L 48" x H 6"
- 8FT** | W 6" x L 96" x H 6"
- Custom Length** | Consult Factory

### FEATURES

- Construction:** Die-formed and welded 22-gauge cold rolled steel
- Lens:** Snap In Frosted Acrylic
- Mounting:** 48" Adjustable Aircraft Cable, 3 Wire Power feed/cable  
*White or Silver Finish Pendant supplied with a White Cable.*  
*Black Finish Pendant supplied with a Black Cable.*
- Dimming Driver:** 0-10V (100-10%) 120-277V 5-Wire or Incandescent 120V 2-Wire
- CRI:** 83
- Life:** 50,000 Hours
- Listings:** cETLus Listed, Title 24 Listed



## ORDERING INFORMATION Example: (12166-2-35K-D10-WH-EM)

Model	Length   Wattage   Lumens	Color Temp	Dimming Driver	Finish	Options
<b>12166</b> i66 Pendant	<b>2</b> 2 Foot   30 Watts   3400 Lumens	<b>35K</b> 3500K	<b>D10</b> 120-277V 5-Wire 0-10V (100% -10%)	<b>WH</b> White <b>BK</b> Black <b>SL</b> Silver	<b>CRWK</b> Continuous Row Wire Kit <b>EM</b> Emergency Backup Battery <b>DS</b> Integrated Daylight Sensor
	<b>4</b> 4 Foot   36 Watts   4200 Lumens	<b>40K</b> 4000K			
	<b>8</b> 8 Foot   72 Watts   8400 Lumens	<b>50K</b> 5000K			
		<b>Commercial</b>	<b>INC</b> 120V 2-Wire Incandescent (100%-1%)		
		<b>Industrial</b>			