

Project Name:

Type:

Quantity:

Alcon 12200-2-S RFT Narrow Linear Ceiling Surface-Mounted LED Light

## FIXTURE SPECIFICATIONS

### INTENDED USE

The architectural-grade, 2-inch wide lens, linear surface ceiling light delivers continuous lines and clear, high-CRI LED light to commercial and residential interior lighting. Our modern 120-277V, slim profile and contemporary design provides up to 4,200 lumens per 8-foot run. The exceptional performance and versatility are ideal for offices, classrooms, conference rooms, museums, retail outlets and hospitality interiors.

### AVAILABLE LENGTHS

<b>2FT</b>		<b>W</b> 2.375" x <b>L</b> 24" x <b>H</b> 3.25"
<b>4FT</b>		<b>W</b> 2.375" x <b>L</b> 48" x <b>H</b> 3.25"
<b>8FT</b>		<b>W</b> 2.375" x <b>L</b> 96" x <b>H</b> 3.25"



### FEATURES

**Construction:** Die-formed and welded 22-gauge cold rolled steel


**Lens:** Snap-in frosted acrylic

**Dimming Driver:** 0-10V (100-10%) 120-277V 5-wire or incandescent 120V 2-wire

**CRI:** 83

**Life:** 50,000 Hours

**Listings:** cETLus Listed, Title 24 Listed



## ORDERING INFORMATION Example: (12200-2-S-2-35K-BK-D10-CRWK)

Model	Length   Wattage   Lumens	Color Temp	Finish	Dimming Driver	Options
<b>12200-2-S</b> RFT Surface	<b>2</b> 2 Foot   15 Watts   1700 Lumens	<b>35K</b> 3500K	<b>WH</b> White <i>Standard</i>	<b>(Blank)</b> Non-Dimming <i>Standard</i> <b>D10</b> 120-277V 5-Wire 0-10V (100% -10%) <b>INC</b> 120V 2-Wire Incandescent (100%-1%)	<b>EM</b> Emergency Backup Battery <b>DS</b> Integrated Daylight Sensor
	<b>4</b> 4 Foot   18 Watts   2100 Lumens	<b>40K</b> 4000K	<b>BK</b> Black		
	<b>8</b> 8 Foot   36 Watts   4200 Lumens	<b>50K</b> 5000K	<b>SL</b> Silver		