

**Project Name:** Type:

**Quantity:** 

SHOP NOW

### **FIXTURE SPECIFICATIONS**

### **INTENDED USE**

The commercial-grade, 4-inch wide lens opening, linear surface ceiling light delivers continuous lines and clear, powerful, high-CRI LED light to commercial and residential interior lighting. Our modern 120-277V, slim profile and contemporary design provides up to 8,400 lumens per 8foot run. The exceptional performance and versatility are ideal for offices, classrooms, conference rooms, museums, retail outlets and hospitality interiors. This linear ceiling light comes in standard lengths of 2-feet, 4-feet and 8-feet and can be connected for continuous runs of any length.

## **AVAILABLE LENGTHS**

2FT | W 4" x L 24" x H 4" **4FT | W** 4" x **L** 48" x **H** 4"

8FT | W 4" x L 96" x H 4"

# **FEATURES**

Construction: Die-formed and welded 22-gauge cold rolled steel

**Lens:** Snap-in frosted acrylic

**Mounting:** 48" adjustable aircraft cable, 3-wire power feed/cable

White or Silver finish pendant supplied with a white cable.

Black finish pendant supplied with a black cable.

**Dimming Driver:** 0-10V (100-10%) 120-277V 5-Wire or Incandescent

120V 2-Wire


**CRI:** 83

Life: 50,000 Hours

Listings: cETLus Listed, Title 24 Listed

Warranty: 1 Year Carefree for Parts & Components

(Labor Not Included)













# ORDERING INFORMATION Example: (12200-4-S-4-35K-D10-WH-EM)

Model -	Length   Wattage   Lumens	Color Temp		Dimming Driver	Finish -		Options -	
<b>12200-4-S</b> RFT Surface	2 <sup>1</sup> 2 Foot   30 Watts   3400 Lumens 4 4 Foot   36 Watts   4200 Lumens 8 8 Foot   72 Watts   8400 Lumens	Commercial 35K 40K Industrial	3500K 4000K 5000K	(Blank) Standard Non-Dimming D10 120-277V 5-Wire 0-10V (100% -10%) INC 120V 2-Wire Incandescent (100%-1%)	WH BK SL	White Black Silver	EM DS	Emergency Backup Battery Integrated Daylight Sensor
								1 Not available on the 2' fixture