

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade decorative Architectural LED Ring Light delivers continuous clean lines and clear circle light to commercial, hospitality and residential interior lighting applications. Our modern, slim profiles and stylish hanging lights designs offer excellent direct lighting, indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. The ring light ring chandelier is available in multiple lengths and several finishes.

DETAILS

W 1.4" x **Depth** 1.1"

Standard Canopy: 10" x 2.25"

Remote Canopy: 3" x .45"

Pendant: 8' adjustable aircraft cable/power cord included (*custom length available*)

Construction: Extruded aluminum outer housing
Adjustable power cord and AC cables with push button grippers standard

Lens: Opal Acrylic diffuser

Reflector: Glare-free, one piece, heavy gauge aluminum

Power Cable: Grey finish jacket

Mounting: All standard J-boxes


ADDITIONAL FEATURES

Voltage: 120/277


CRI: 90

Dimming: 0-10V, dims to 1%

Emergency: 90 minutes minimum,
Remote install only





S – Standard




R – Remote

RD - Braided Red
Architectural Cable Mount



Cross Section



ORDERING INFORMATION Example: (12254-2-30K-SL-WH-S-EM)

Model	LED Downlight	Color Temp	Finish	Cable Finish	Mounting	Options
12254	2 2 ft 26 Watts 2166 Lumens	30K 3000K	SL Silver	WH White	S Standard	EM 7W Emergency Battery Pack
	3 3 ft 39 Watts 3250 Lumens	35K 3500K	BK Black	GR Gray	R Remote	XX Custom AC Cable/Power Cord (25' Max)
	4 4 ft 52 Watts 4333 Lumens	40K 4000K	WH White	RD Braided Red		
	5 5 ft 65 Watts 5416 Lumens					