



Project Name:

Type: Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

Featuring an elegant and original design, this large, architectural-grade LED half circle pendant affords powerful downlighting and uplighting. Designed with hospitality, residential and commercial interiors in mind, our light comes in extruded aluminum outer housing with a glare-free reflector. The distinctive light includes an adjustable aircraft cable.


FEATURES


Construction: Extruded aluminum outer housing Adjustable power cord and AC cables with push button grippers are standard Dimensions: Width 1.10" x Depth 2.20" Remote Canopy: 3.80" D x 0.45" H Lumen Output: Direct 50 Pendant: 8' adjustable aircraft cable/power cord included (Custom length available, consult MFG) **Lens:** White frosted acrylic diffuser **Reflector:** Glare-free, one piece, heavy gauge aluminum Mounting: All standard J-boxes Voltage: 120/277VAC **CRI:** 90 **Dimming:** 0-10V (100-1%) **Remote Emergency:** 90 Minutes **Listings**: cUL listed for dry locations only. ASSEMBLED



ORDERING INFORMATION Example: (12258-3-30K-SL-WH)







Remote Driver Canopy 3.80" D x 0.45" H

Mode	l Size Wattage Lumens	Color Temperature	Finish	Cord Finish	Options
1225	 3 3 3 Foot 44 W 2500L Direct / 2500L Indirect 6 6 Foot 98 W 4100L Direct / 4100L Indirect 	30K 3000K 35K 3500K 40K 4000K	SL Silver BK Black WH White	WH White GR Gray	EM7 7W Remote Emergency Back-Up Battery EM12 12W Remote Emergency Back-Up Battery XX Custom AC Cable/Power Cord (25' Max)



COLOR TEMPERATURE GUIDE

