

Project Name:	Type:	Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade Canon Architectural LED Adjustable Beam Track **Light Fixture** delivers direct track lighting to commercial, hospitality and residential interior ceiling track lighting applications. Architecturally styled Cylinder LED track lights feature small, unobtrusive size and are highly adjustable. Our modern LED track light fixture designs offer excellent illumination, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more. **PRODUCT FAMILY**

Track Channel 13000-TC **Linear Connector** 13000-LC **Outlet Adapter** 13000-OA

Slope Ceiling Track Adapter 13000-SC

T-Bar End Feed 13000-TB

13000-FC Floating Canopy Connector

13000-EC **End Cap**

13000-LC Live End with Canopy

Live End 13000-LE L-Connector 13000-L T-Connector 13000-T X-Connector 13000-X Mini Connector 13000-MC

Cord and Plug Connector 13000-CP

13000-PA **Pendant Adapter Conduit Connector** 13000-CC **Conduit Continuation Kit** 13000-CK

FEATURES

Construction: Solid die-cast aluminum

Adjustability: 90° Adjustable Track head with 358° rotation Optics: Lens provides smooth lumen output at standard 38°

Wattage: 20 Watts Lumens: 1600 Lumens **Beam Angle Range:** 20°-50°

Installation: H-Track is standard; all tracks have adjustable adapters for use

with single or two-circuit tracks. J-Style or L-Style is optional.

CRI: 90+ Voltage: 120V

Color Temperature: 3000K Dimming: TRIAC and ELV (100-10%)

Warranty: 5 Years Carefree for Parts & Components (Labor Not Included)

Listings: ETL, RoHS Compliant,













ORDERING INFORMATION Example: (13301-SM-BK-H)

Model **Finish** Track **H** H - Style Standard Black 13301 J - Style WH White Canon L L-Style



SHOP NOW

