



SPECIFICATION SHEET

Project Name:

Ē







FIXTURE SPECIFICATIONS

INTENDED USE

The Illusione 3-Inch Architectural LED Square Trimless Recessed Light Fixture is designed for lasting durability and beauty while providing quality and energy efficient lighting for low to medium ceilings. The Illusione is an ideal solution for clear and bright lighting in retail, hospitality, commercial, and high-end residential settings.

W 3" x **L** 3 3/16" x **H** 3 1/8"

PRODUCT FAMILY

- 14006 | Lensed Recessed Down Light
- 14006-2 | Open Reflector Recessed Down Light
- 14006-3 | Lensed Wall Wash
- 14006-4 Open Reflector Wall Wash



FEATURES

Construction: Seamless die-cast with IC rated housing with loosefill blown and rolled insulation Collar Bracket: 90° rotation in 5° increments (pre-drywall installation) Finish: White Lamp Holder: 35° tilt 1 1/2" Vertical lamp source adjustment Mounting: Housing for new construction installation only (2) 24" adjustable hangar bars w/ 90° repositioning Lens: Frosted Power Connection: LED lamp array is replaceable via on board quick disconnect terminal Voltage: 120/277 UNV Wattage: 12W (IC Rated), 19W (Non-IC Rated) Lumens: 600 lms (IC Rated), 1200 lms (Non-IC Rated) Driver: Electronic direct current LED driver integrally mounted in electric junction box CRI: 80 standard Life: 50,000 hours Listings: ETL listed, Title 24 / JA8 compliant certified by CEC

ORDERING INFORMATION Example: (14006-2-12W-NF45-27K)

Model _	Wattage/Lumens		Be	Beam Spread		Color Temp		Dimming		Options	
14006 14006-2 14006-3 14006-4	12W 19W	12W/600 Ims (IC Rated) 19W/1200 Ims (Non-IC Rated)	SP25 ¹	45° Narrow Flood 25° Spot 60° Wide Flood	27K 27C 30K 35K 40K WD	2700K 2700K (90+ CRI) 3000K 3500K 4000K Warm Dimming (1850K-2700K)	Blank 010	Non-Dimming 0-10V, 5-Wire	EM25X	Wet Location 25W External Emergency Battery (Above Ceiling Access Required) available for 12W	