roject Name:	Type:	Quantity:

INTENDED USE

Including a snap-on mounting bracket for an easy installation to T-Bars, our low profile LED T-bar grid light is made from high-quality aluminum. This surface mount profile is manufactured with a frosted diffuser for maximum lumen output and wide beam distribution.

FEATURES

Construction: Aluminum construction with frosted

Installation: Factory assembled for easy and fast

installation. Wire is Back-Feed.

Driver: Remote non-dimming transformer is provided home run required at every 16'

Voltage: 24V input Lumen: 310L per foot Wattage:5W per foot

WiFi Controls (iOS/Android):

Mobile App: Easy Home Smart Home

DMX Wall App: WiFi 104

CRI:90+


Life:50,000 Hours

Listings: cULus, CA Title 24 JA8, Assembled in USA Warranty: 5 years carefree for parts & components

(labor not included)









Includes 15/16" T-bar mounting brackets

ORDERING INFORMATION EXAMPLE: (14027-RGBW-2-WH-RGB+27K-RF)

Model	Length	Finish	Color Temperature	Controllers
14027-RGBW	2 2 Foot 10W 620L 4 4 Foot 20W 1,240L 6 6 Foot 30W 1,860L 8 8 Foot 60W 2,480L	WH White BK Black	RGB+27K RGB + 2700K RGB+30K RGB + 3000K RGB+40K RGB + 4000K RGB+50K RGB + 5000K	WIFI Mobile Application + WiFi RF RF Remote Control (White) DMX DMX Wall Control (White) DMX-W-WIFI DMX Wall Control (White) + WiFi DMX-B-WIFI DMX Wall Control (Black) + WiFi



RGBW CONTROLLERS



RF Remote Control 6.38" L × 1.65" W × 0.59" H



DMX Wall Control

5,20" L x 7.09" W x 1.38" H



Mobile Application + WiFi



WiFi-104
iOS + Android

DMX Wall Control + WiFi

5.75" L x 4.17" W x 0.43" H



