



Project Name: Type: **Quantity:**

FIXTURE SPECIFICATIONS

INTENDED USE

Alcon Lighting's 14035 High-Performance Low-Profile 2-Inch Adjustable Square Recessed LED light fixture has been designed to offer high light output and provide high CRI increasing the light quality of a space. UL listed for wet locations the 14035 is suitable for hotels, condos and apartments.

ADDITIONAL FEATURES

Suitable for use in fixtures installed in insulated ceilings. Suitable for new construction and remodel housings.

Construction: Die-cast aluminum body that provides superior thermal management Lens: PC lens for even distribution

Life: 50.000 Hours L70 **Dimmable:** Triac/ELV Beam Angle: 36° Adjustability: 25° Wattage: 9W Voltage: 120V Lumens: 850 lumens

CRI: 90+

Color Temperature: 2700K

Warranty: 5 years carefree for parts and

components (labor not included)

Listings: UL listed for wet locations, Title 24

(JA8-2016-E), Energy Star certified
















2" IC Airtight Construction Housing Height: 4" Opening: 2 1/2"



2" Non-IC **Construction Housing** Height: 3 1/2" Opening: 2 1/2"



2" Remodel Housing Height: 3 1/2" Opening: 2 1/2"

ORDERING INFORMATION Example: (14035-27-IC)

Model	Col	or Temp		Housing
14035	27	2700K, 9 watts 850 lumens	IC NIC	IC Airtight New Construction Non-IC New Construction
			R	Remodel

	Illuminance at a Distance Center Beam fc Beam Width						
2.0 R	347 fc	l.	1.3 ft	1.3 ft			
4.0R	86.8 fc	l.	2.6 ft	2.6 ft			
6.0R	38.6 fc		4.0 ft	4.0 ft			
8.0A	21.7 fc		5.3 ft	5.3 ft			
10.0R	13.9 fc		6.6 ft	6.6 ft			
12.0R	9.65 fc		7.9 ft	7.9 ft			
■ Vert. Spread: 36.5° ■ Horiz. Spread: 36.4°							

Cone of Light based on mounting height of 12'