


FEATURES & SPECIFICATIONS

INTENDED USE


Alcon Lighting's 14037 High Performance Low Profile 2 Inch Recessed LED light fixture has been designed to offer high light output and provide high CRI increasing the light quality of a space. UL listed for wet locations the 14037 is suitable for hotels, condos and apartments.

ADDITIONAL FEATURES


- IC Airtight, Non IC Airtight or Remodel Housing options available with quick connect for easy light engine installation
- IC Airtight Double Wall New Construction Housing option for use in insulated ceilings
- Die-cast construction
- Life Span: 50,000 Hours L70
- Dimmable: Triac/ELV
- Beam Angle: 36°
- 9 Watt
- Lumens: 580
- CRI: 90+
- Color Temperature: 2700K
- 120V
- UL listed for Wet Locations



2" IC Airtight
Construction Housing
Height: 4"
Opening: 2 1/2"



2" Non-IC
Construction Housing
Height: 3 5/8"
Opening: 2 1/2"



2" Remodel Housing
Height: 3 1/2"
Opening: 2 1/2"

Listings:



Ordering Information:

Example: (14037-27-IC)

Model

14037

Color Temp.

27

2700K, 9W
580 Lumen

Housing

IC

IC Airtight New Construction

NIC

Non-IC New Construction

R

Remodel

Illuminance at a Distance			
	Center Beam fc	Beam Width	
2.0ft	347 fc	1.3 ft	1.3 ft
4.0ft	86.8 fc	2.6 ft	2.6 ft
6.0ft	38.6 fc	4.0 ft	4.0 ft
8.0ft	21.7 fc	5.3 ft	5.3 ft
10.0ft	13.9 fc	6.6 ft	6.6 ft
12.0ft	9.65 fc	7.9 ft	7.9 ft

■ Vert. Spread: 36.5°
■ Horiz. Spread: 36.4°

Cone of Light based on mounting height of 12'