

## FEATURES & SPECIFICATIONS


### INTENDED USE

Alcon Lighting's 14039 High Performance Low Profile 2 Inch Adjustable Recessed LED light fixture has been designed to offer high light output and provide high CRI increasing the light quality of a space. UL listed for wet locations the 14039 is suitable for hotels, condos and apartments.




### ADDITIONAL FEATURES


- IC Airtight, Non IC Airtight or Remodel Housing options available with quick connect for easy light engine installation
- IC Airtight Double Wall New Construction Housing option for use in insulated ceilings
- Die-cast construction
- Life Span: 50,000 Hours L70
- Dimmable: Triac/ELV
- Beam Angle: 36°
- 9 Watt
- Lumens: 580
- CRI: 90+
- Color Temperature: 2700K
- 120V
- UL listed for Wet Locations



2" IC Airtight Construction Housing  
Height: 4"  
Opening: 2 1/2"



2" Non-IC Construction Housing  
Height: 3 5/8"  
Opening: 2 1/2"



2" Remodel Housing  
Height: 3 1/2"  
Opening: 2 1/2"

### Listings:



### Ordering Information:

Example: (14039-27-IC)

Model	Color Temp.	Housing
<input type="text" value="14039"/>	<input type="text" value="27"/>	<input type="text" value="IC"/>
14039	27 2700K, 9W 580 Lumen	IC IC Airtight New Construction NIC Non-IC New Construction R Remodel

	Illuminance at a Distance	
	Center Beam fc	Beam Width
2.0ft	347 fc	1.3 ft
4.0ft	86.8 fc	2.6 ft
6.0ft	38.6 fc	4.0 ft
8.0ft	21.7 fc	5.3 ft
10.0ft	13.9 fc	6.6 ft
12.0ft	9.65 fc	7.9 ft

■ Vert. Spread: 36.5°  
■ Horiz. Spread: 36.4°

Cone of Light based on mounting height of 12'