

FIXTURE SPECIFICATIONS

INTENDED USE

With a Color Rendering Index (CRI) over 80 and an extruded, diecast metal body suspended from an aircraft cable with a frosted, glare-free lens, this architectural-grade sky panel contains multiple planes for endless configurations for clarity through LED pendant lighting. This daylight harvesting LED high bay light provides both uplighting and downlighting to commercial, hospitality and residential interiors. Dimming, emergency battery backup and variable lumens, color temperatures and voltages included.

FEATURES

Construction: Die-cast extruded aluminum body

Aircraft Cable Length: 144"

Lens: Glare free snap-in frosted lens

Driver: 0-10V Dimming

Voltage: 120-277V 50/60 Hz

CRI: 80+


Power Factor: >0.90

Warranty: 1 years carefree for parts & components (labor not included)


Listings: Made in the USA




DIMENSIONS




2x2 Triangles



2X2 Squares



1X4 Squares



2X4 Squares

ORDERING INFORMATION Example: (14065-22TRI-D120-BK-35K)

Model	Style	Wattage Lumens	Bracket Finish		Color Temp	Options
14065	22TRI 2x2 Triangles	D120 120W 15000 lms	BK Black	YL Yellow	35K 3500K	EM14 Integral 10W Emergency battery backup
	22SQ 2X2 Squares	D160 160W 20000 lms	GBK Glossy Black	OR Orange	40K 4000K	EM12¹ 12W Emergency battery backup
	14SQ 1X4 Squares	D160 160W 20000 lms	SL Silver	DR Dark Red	50K 5000K	EM20 Remote 20W Emergency battery backup
	24SQ 2X4 Square	D300 300W 37500 lms	BR Bronze	RD Red		
			IR Iron	BL Blue		


¹ Integral for 2x4 Square Style. Remote for all other Styles.

Available Finishes

Fixture Finishes

	White
	Black
	Silver

Bracket Finishes

	Black
	Glossy Black
	Silver
	Bronze
	Iron
	Yellow
	Orange
	Dark Red
	Red
	Blue



COLOR TEMPERATURE GUIDE

