**SHOP NOW** ⟩

**Project Name:**        **Type:**      **Quantity:**

## FIXTURE SPECIFICATIONS

### INTENDED USE

The Illusione 4-Inch architectural LED trimless recessed light fixture is designed for lasting durability and beauty while providing quality and energy efficient lighting for low to medium ceilings. The Illusione is an ideal solution for clear and bright lighting in retail, hospitality, commercial, and high-end residential settings.

### FEATURES

**Construction:** Heat-dissipating, die-cast aluminum.
**Multi-Optic:** 60° optics factory installed. 38° and 25° optics included.
**Mounting:** Reflector includes friction blades to mount securely in a trimless mud ring.
**CRI:** 90+
**Wattage:** 14W
**Dimming:** 120V Triac ELV dimming is standard. Optional 120-277V universal dimming system compatible with most 3-wire ELV, 2-wire incandescent and 5-wire 0-10V fluorescent dimmers available.
**Operating Temperature:** 32˚F ~ 104˚F (0˚C ~ 40˚C) ambient temperature
**Lifetime:** 50,000 hours L70
**Warranty:** 5 years carefree for parts & components (labor not included)
**Listing:** cULus, RoHS, Energy Star, 2016 Title-24, Assembled in the USA, Suitable for Wet Location (Only for 14074-R-ADJ)

2-3/4"      3-1/4"      3-1/4"

**Square Trimless Mud Ring (Included)**      **Round Trimless Mud Ring (Included)**

**IC / CH** - Housing

4"    4-1/4" Ceiling Cut-Out

7-5/8"

12"

**FA**- Optional Flange Accessory

**HEX** - Optional Hex Cell Louver

SPEC GRADE | DIMMABLE | c UL us LISTED | WET LOCATION SUITABLE | RoHS COMPLIANT | TITLE 24 | ENERGY STAR | LIMITED 5-YEAR WARRANTY | ASSEMBLED IN THE USA

## ORDERING INFORMATION   Example: (14074-RF-10-27K-WH-IC-EMT)

| Model | Shape | Lumens | Color Temp | Finish | Housing | Dimming | Options |
|---|---|---|---|---|---|---|---|
| **14074** | **RF** Round Fixed | **10** 1000 lms | **27K** 2700K | **WH** White | **IC** IC Air-Tight | **(Blank)** Standard 120V (Triac/ELV) | **HEX** Hex Cell Louver |
| | **RA** Round Adjustable | | **30K** 3000K | **BK** Black | **CH** Chicago Plenum | **UNI** Universal 120-277V (Triac/ELV/0-10V) | **EMT**[2] Remote Emergency Back-Up Battery with Test Switch |
| | **SF** Square Fixed | | **35K** 3500K | **SL** Silver | | | **FA**[3] Flange Accessory |
| | | | **40K** 4000K | **BR** Bronze | | | |
| | | | | **WB**[1] White Reflector / Black Head | | | |
| | | | | **WS**[1] White Reflector / Silver Head | | | |

[1] Only compatible with Round Adjustable Option

[2] EMT option not available with CH (Chicago Plenum housing)

[3] Flange Accessory will match fixture finish