Alcon Lighting 14075

Recessed

Flat Panel Architectural Troffer LED Light

# SPECIFICATION SHEET

See to sat Manager	T	O
Project Name:	lype:	_ Quantity:

#### **INTENDED USE**

With the capacity to switch wattage and color temperature, a frosted, impact-resistant flat lens and 100,000 hours of life, the LED light offers abundant light in a slender, versatile and modern design that's ideal for today's interior spaces. Our product is made for recessed, suspended and surface-mounted applications. Perfect for the office, conference room, corridor, lab or public space.

#### **DIMENSIONS**

Height: 1.625" (41mm)

### **FEATURES**

Color Temperature: Features the ability to switch color temps from

3500K, 4000K and 5000K.

Construction: Aluminum housing

Lens: Satin White Finish: White

Voltage: 100-277V 50/60 Hz constant current

Life: L70 - 50,000 Hrs

Lens: Frosted white impact-resistant lens

Dimming: 0-10V dimming to 10%

Life: 100,00 hours

**CRI:** 80+

Operating Temperature: -4°F ~ 113°F (-20°C ~ 45°C)

Listing: cULus, DLC, Assembled in the USA (optional), UL 1598 suitable for damp locations, type IC, UL 8750 LED equipment in

**Lighting Products** 

Warranty: 5 Years Carefree for Parts & Components

(Labor Not Included)

Wattage and color temperature switches are accessible on the driver box






















ORDERING INFORMATION Example: 14075-14-EM10

Model		Size   Wattage   Lumens	Options	
14075	14 1x4	25W, 30W, 40W   4400lm, 4440lm, 4480lm	<b>EM8</b> 8W Emergency Battery	
	<b>22</b> 2x2	25W, 30W, 40W   4400lm, 4440lm, 4480lm	<b>EM16</b> 16W Emergency Battery	
	24		EM25 25W Emergency Battery	
	2x4	30W, 40W, 50W   5500lm, 5550lm, 5600lm	<b>p</b> 1 Prismatic Lens	

1 Replaces standard Satin White Lens



## **COMPATIBLE DIMMERS**

	LIGHTING	<b>%LUTRON</b>	<b>LEVITON</b> <sub>®</sub>
0-10 V	<u>2100</u> 2101	Diva DVTV	IP-710-DL
0 10 0	<u>2102</u>		

