



### FIXTURE SPECIFICATIONS

#### INTENDED USE

The **Continuum 23 Architectural Linear LED Ceiling to Wall Lighting Fixtures** bring clean lines and clear light to commercial LED or residential office lighting interiors. Our ceiling to wall lighting fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

#### PRODUCT FAMILY

- 12100-44-R-L | Continuum 44
- 12100-66-R-L | Continuum 66

#### FEATURES

- Construction:** Die-Formed and Welded 22-Gauge Cold Rolled Steel
- Lens:** Snap In Frosted Acrylic
- LED Board:** Even and diffuse light that reduces the need for multiple optical layers, simplifying the luminaire design and maximizing optical efficiency
- Voltage:** 120-277
- Dimming:** 0-10V
- Warranty:** 5 Years
- Listing:** ETL Listed



### ORDERING INFORMATION Example: (12100-23-R-L-R-C12-C12-7W-27K-EM)

Model	Ceiling Length	Wall Length	Wattage   Lumens/Ft	Color Temp	Finish	Optional
12100-23-R-L-R Trimless T-Bar Grid Ceiling	<b>C12</b> 12"	<b>W12</b> 12"	<b>7W</b> 7 watts   700 lms	<b>27K</b> 2700K (+90 CRI)	(Required for RF only)	<b>DS</b> Daylight Sensor
	<b>C24</b> 24"	<b>W24</b> 24"	<b>12W</b> 12 watts   1200 lms	<b>30K</b> 3000K (83 CRI)	<b>NR</b> Not Required	<b>EM</b> Emergency Ballast
12100-23-R-L-RR Trimless Drywall Hard Ceiling	<b>C36</b> 36"	<b>W36</b> 36"		<b>35K</b> 3500K (83 CRI)	<b>WH</b> White	
	<b>C60</b> 60"	<b>W60</b> 60"		<b>40K</b> 4000K (83 CRI)	<b>BK</b> Black	
12100-23-R-L-RF Flanged Drywall Hard Ceiling	<b>C72</b> 72"	<b>W72</b> 72"		<b>50K</b> 5000K (83 CRI)	<b>SL</b> Silver	
	<b>C84</b> 84"	<b>W84</b> 84"				
	<b>C96</b> 96"	<b>W96</b> 96"				