


Recessed/ Flangeless for T-Bar



Recessed/ Flanged



Recessed/ 1/2" Flanged



FIXTURE SPECIFICATIONS

INTENDED USE

The **Continuum IV Architectural Linear LED Ceiling to Wall Lighting Fixtures** bring clean lines and clear light to commercial LED or residential office lighting interiors. Our ceiling to wall lighting fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

PRODUCT FAMILY

- 14100-2 | Continuum II
- 14100-6 | Continuum VI

FEATURES

- Construction:** Die-Formed and Welded 22-Gauge Cold Rolled Steel
- Lens:** Snap In Frosted Acrylic
- LED Board:** Even and diffuse light that reduces the need for multiple optical layers, simplifying the luminaire design and maximizing optical efficiency
- Voltage:** 120-277
- Dimming:** 0-10V
- Warranty:** 5 Years
- Listing:** ETL Listed



THIS PRODUCT IS ONLY TO BE INSTALLED BY A QUALIFIED TECHNICIAN IN ACCORDANCE WITH NATIONAL AND LOCAL ELECTRICAL CODES.

ORDERING INFORMATION Example: (14100-4-R-C12-C12-7W-27K-EM)

Model	Ceiling Length		Wall Length		Wattage Lumens/Ft	Color Temp	Finish	Optional
14100-4-R Trimless T-Bar Grid Ceiling	C12	12"	W12	12"	7W 7 watts 700 lms	27K 2700K (+90 CRI)	(Required for RF only)	DS Daylight Sensor
	C24	24"	W24	24"	12W 12 watts 1200 lms	30K 3000K (83 CRI)	NR Not Required	EM Emergency Ballast
14100-4-RR Trimless Drywall Hard Ceiling	C36	36"	W36	36"		35K 3500K (83 CRI)	WH White	
	C60	60"	W60	60"		40K 4000K (83 CRI)	BK Black	
14100-4-RF Flanged Drywall Hard Ceiling	C72	72"	W72	72"		50K 5000K (83 CRI)	SL Silver	
	C84	84"	W84	84"				
	C96	96"	W96	96"				