


FIXTURE SPECIFICATIONS

INTENDED USE

The **Continuum VI Architectural Linear LED Ceiling to Wall Lighting Fixtures** bring clean lines and clear light to commercial LED or residential office lighting interiors. Our ceiling to wall lighting fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

PRODUCT FAMILY

- 14100-2** | Continuum II
- 14100-4** | Continuum IV



FEATURES

- Construction:** Die-Formed and Welded 22-Gauge Cold Rolled Steel
- Lens:** Snap In Frosted Acrylic
- LED Board:** Even and diffuse light that reduces the need for multiple optical layers, simplifying the luminaire design and maximizing optical efficiency
- Voltage:** 120-277
- Dimming:** 0-10V
- Warranty:** 5 Years
- Listing:** ETL Listed



ORDERING INFORMATION Example: (14100-6-R-C12-C12-7W-27K-EM)

Model	Ceiling Length	Wall Length	Wattage Lumens/Ft	Color Temp	Finish	Optional
14100-6-R Trimless T-Bar Grid Ceiling	C12 12"	W12 12"	7W 7 watts 700 lms	27K 2700K (+90 CRI)	(Required for RF only)	DS Daylight Sensor
	C24 24"	W24 24"	12W 12 watts 1200 lms	30K 3000K (83 CRI)	NR Not Required	EM Emergency Ballast
14100-6-RR Trimless Drywall Hard Ceiling	C36 36"	W36 36"		35K 3500K (83 CRI)	WH White	
	C60 60"	W60 60"		40K 4000K (83 CRI)	BK Black	
	C72 72"	W72 72"		50K 5000K (83 CRI)	SL Silver	
14100-6-RF Flanged Drywall Hard Ceiling	C84 84"	W84 84"				
	C96 96"	W96 96"				