

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade Basic Architectural LED Recessed Troffer fixtures bring clean lines and clear light to commercial LED or residential office lighting interiors. Our sleek, stylish fixtures offer highly effective and efficient lighting solutions for hotels, offices, retail outlets, restaurants, and more.

AVAILABLE SIZES

- 2x2** | W 11.75" x L 24" x H 4"
- 2x4** | W 23.75" x L 24" x H 4"
- 1x4** | W 11.75" x L 48" x H 4"



FEATURES

- Construction:** Die-formed and embossed code 22 gauge steel housing Access plate to simplify installation
- Finish:** High reflectance baked white enamel
- Lens:** Clear 0.10 thick A12 Acrylic
- Voltage:** 120-277V (50/60 Hz) Constant Current
- Support:** Recessed Inverted T-Bar Ceilings. Grid Mount.
- Life:** 50,000 Hrs
- CRI:** 80+
- Operating Temperature:** -4°F~122°F
- Lamp Included
- Listings:** UL Listed
- Warranty:** 5 Years Carefree for Parts & Components (Labor Not Included)



ORDERING INFORMATION Example: (14115-22-30K-ND)

Model	Size	Wattage Lumens	Color Temperature	Dimming	Options
14115	22 2x2	<small>2x2 Options</small> 24 24 Watts 2700lms	30K	ND Non-Dimming	EM Emergency Backup Battery
		28 28 Watts 3200lms	35K		
		35 35 Watts 3900lms	3500K		
	24 2x4	<small>2x4 Options</small> 35 35 Watts 4600lms	40K	DM10 0-10V Dimming (100%-10%)	
		40 40 Watts 5300 lms	50K		
		14 1x4	<small>1x4 Options</small> 35 35 Watts 4300 lms		DM1 5-Wire 0-10V Dimming (100%-1%)
			48 48 Watts 5800 lms		

FIXTURE DIMENSIONS

