Quantity:

Project Name:

Irimless

Pulldown Light

INTENDED USE

This 2" LED lighting fixture telescopes from trimless housing with a capacity to tilt in rotation to showcase specific items. The trim is plastered into the ceiling. With no visible trim, the lights are tucked away, appearing as though they are built into the ceiling, offering a polished, premium look. Our recessed product suits remodeled or new construction installation. The round, cylindrical lighting is additionally designed to adhere to existing paneled ceilings (of any thickness) or sheet rock.

PRODUCT FAMILY

14121-DIR Trimless Round Direct
14121-ADJ Trimless Round Adjustable
14121-WW Trimless Round Wall Wash
14121-PL Trimless Round Pull Down
14131-DIR Trimless Round Direct "Shallow"
14131-WW Trimless Round Wall Wash "Shallow"

FEATURES

Construction: Designed to Secure to Existing Sheet Rock or Panel Ceilings of any thickness. For a smooth planar surface Mudding may be applied right up to the edge of the fixture

Diameter: 2.5" Lumens: 650 (7W)

Trim Ring: Reflector and Trim Secure to Sheet Rock or Housing

Frame with Drywall Screws Secured to Trim Ring

Optics: Chip On Board LED Tilting: 75° with 340° rotation

Voltage: 120V

Dimming: TRIAC dimming to 10% includes an 18-gauge pre-wired

aluminum Junction Box

CRI: 90

Life: 50,000 Hours (L70)


Warranty: 5 Years Carefree for Parts and Components (Labor not included). A reduced LED lamp life and a Warranty void will result in installations where temperatures exceed 35°C


Listings: ETL/cETL listed to UL1598 & UL8750


Title 24 / JA8 Compliant Certified NYC approved: Calendar #41937. Suitable for damp locations



Type:





















ORDERING INFORMATION Example: (14121-PL-B20-27K-MW-IC-WL)

Model

14121-PL

Adjustable
Trimless
Round
Pull Down

Beam Spread

B20 20° Spot

B40 40° Flood

Color Temp

27K 2700K

30K 3000K

8000K **BK** B

WH White

35K 3500K

sh Housing

NC New Construction Non-IC Ratedn



