

INTENDED USE

The specification grade 15204 Hudson is the ideal solution for warehouse, gymnasium, or other mid to high-ceiling applications where high output LED lighting is desired.

FEATURES

Construction: .064" thick spun aluminum cylinder supplied with aluminum and polycarbonate reflector options.

Mounting: Adjustable aircraft cable with either straight or coiled cords, hard stem which can accommodate sloped ceilings with a 45° swivel.

Reflector: Polycarbonate reflector provides more rugged performance in an abusive environment. Aluminum heavy gauge, high purity, spun aluminum. Polyester powdercoat finish.

CRI: 80+ Standard, 90+ Optional

Voltage: 120-277V for 0-10V Dimming.

120V for TRIAC Dimming.

LED Driver: 0-10V 5-wire dims to 1% and Triac 3-wire dims to 20%.

Life-span: 50,000 hours at L70 standard.

Labels: UL, ETL, CSA, Suitable for Damp Locations. Wet location under covered ceiling.

Warranty: 5 years carefree for parts & components (labor not included)



Flat Clear Lens
(Optional)



Conical Lens
(Optional)



ORDERING INFORMATION Example: (15204-12-11L-27K-AL-WH-AC6-WH-WH-010)

MODEL		15204		
DIAMETER		12 12" Dia.	16 16" Dia.	
LUMENS		11L 1100 15L 1500	20L 2000 30L 3000	40L 4000 50L 5000
COLOR TEMP		27K 2700K 30K 3000K	35K 3500K 40K 4000K	
CRI		(Blank) 80+	9 90+	
SHADE		AL ¹ Aluminum	PL Polycarbonate	
HOUSING FINISH		WH White BK Black	BZ Bronze SL Silver	CC Specify SKU (Pg. 4)
MOUNTING		AC6 6' Aircraft Cable AC10 10' Aircraft Cable AC15 15' Aircraft Cable AC20 20' Aircraft Cable	ST1 1' Stem ST2 2' Stem ST3 3' Stem STxx Specify X in Feet (Max 12')	CAC4 4' Coiled Cord CAC6 6' Coiled Cord CAC10 10' Coiled Cord
MOUNTING FINISH		WH White BK Black	BZ ³ Bronze SL ⁴ Silver	CC Specify SKU (Pg. 7)
CORD FINISH		WH White	BK Black	GR Gray
BOTTOM LENS		(Blank) Open	FL Flat Clear Lens	CL Conical Lens
DIMMING		010 ² 0-10V Dim to 1%	TRI Triac Dim to 20%	
OPTIONS		REM Remote Emergency Battery Backup SC Safety Cable WG Wire Guard HC Die-Cast Hook, 18/5 Cord HCP Die-Cast Hook, 18/5 Cord,NEMA Twist Lock Plug		

¹ Aluminum shade matches housing finish. Interior white finish is standard.



² 0-10V Dimming not available with coiled cord.

³ Bronze finish only available with stem mounting.


⁴ Silver finish only available with stem and aircraft cable mountings.

MOUNTING


FIXTURE DIMENTIONS




AIRCRAFT CABLE



COILED CABLE





STEM




Lumens	Wattage
1100-40K	13.8
1100-27K	14.7
1500-40K	18.8
1500-27K	20.1
2000-40K	25.2
2000-27K	26.4
3000-40K	35.8
3000-27K	37.1
4000-40K	51.0
4000-27K	52.3
5000-40K	56.0
5000-27K	57.4


AVAILABLE FINISHES

				
RBE - ROBIN EGG	TRQ - TURQUOISE	DEU - DARK EUCALYPTUS	HBL - HYDRANGEA BLUE	BLB - BLUE BIRD
				
BRD - BORDEAUX RED	PCL - PINK CORAL	SPK - SUBTLE PINK	SOR - SALMON ORANGE	SSG - SUNSET ORANGE
				
RVT - RED VELVET	PVT - PURPLE VELVET	BVT - BLUE VELVET	WHC - WHITE CRYSTAL	WH - WHITE MATTE
				
WHG - WHITE HIGH GLOSS	TGD - TRANSLUCENT GOLD	BA - BRUSHED ALUMINUM	ACR - ANTIQUE CHROME	SL - MIRROR SILVER SPARKLE
				
MCL - METALLIC CHARCOAL	BZ - BRONZE	BLS - BLACK SCALE	BK - BLACK MATTE	PBK - PIANO BLACK

CORD ONLY FINISHES



BK - BLACK CORD




GR - GREY CORD



WH - WHITE CORD

REFLECTOR ONLY FINISHES



SC - SPECULAR CLEAR



SG - SOFT GLOW CLEAR

COLOR TEMPERATURE GUIDE

				
2700K	3000K	3500K	4000K	5000K
WARM WHITE	SOFT WHITE GLOW	NEUTRAL GLOW	COOL WHITE GLOW	DAYLIGHT GLOW
friendly personal intimate	soft warm pleasing	sociable inviting non-threatening	neat clean efficient	bright cool alert
HOMES LIBRARIES RESTAURANTS	HOMES HOTEL ROOMS LOBBIES RETAIL STORES	EXECUTIVE OFFICES RECEPTION AREAS SUPERMARKETS	OFFICES CLASSROOMS MASS MERCHANDISERS SHOWROOMS	GRAPHICS INDUSTRY HOSPITALS GALLERIES BEAUTY SALONS
✓	✓	✓	✓	✗