



FIXTURE SPECIFICATIONS

INTENDED USE

The **Opto Architectural LED Canopy** features symmetrical light distribution and a heavy duty design to protect against moisture and vandalism. The Opto is a high quality option for parking structures, corridors, gas stations, and other outdoor applications.

SELECTABLE WATTAGE

- 25W** | 2950 lumens
- 40W** | 4720 lumens
- 50W¹** | 6200 lumens

FEATURES

- Construction:** Heavy Duty Die-Cast
- Gasket:** Silicone Sealed to Prevent Moisture and Contaminants
- Lens:** UV Stabilized, Clear Prismatic Polycarbonate
- Distribution:** Type V
- Voltage:** 120-277V
- Wattage:** Select-A-Watt 25W / 40W / 50W
(Field Adjustable / Factory Set at 50W)
- Dimming:** Available with 0-10V Inputs Dimming Down to 10%
- CRI:** 84+
- Power Factor:** >.90
- THD:** < 20%
- Life:** 177,000 Hours
- Max Ambient Temperature:** -40°F (-40°C) - 122°F (50°C)
- Sound Rating:** Class A
- Warranty:** 10 Years
- Listings:** CSA Listed for Wet Location



ORDERING INFORMATION Example: (16004-25W-40K-SLO-30K-BZ-EM)

Model	Color Temp	Finish	Options
16004	40K 4000K	BZ Bronze	HQ Hinged Quick-Mount Bracket
	50K 5000K	WH White	
		BK Black	
		#XXXX³ Custom Color	

¹DLC Listed Wattage
²Please Specify RAL Number