SHOP NOW



Project Name: Type: **Quantity:**

FIXTURE SPECIFICATIONS

INTENDED USE

Illuminate exteriors, such as entrances, stairways, walkways, perimeters, parking garages, storage areas and warehouses, from the ceiling with our wet location-rated product. Equipped in non-corrosive, ultraviolet-resistant white or black resin with a white lens and a dimming option.



FEATURES

Dimensions: 9.375" Diameter x 4.5" Height

Construction: Non-corrosive UV-resistant white or black

resin with white lens

CRI: 120V: 80+, 120-277V: 70+

Operating Temperature: -40F to +104F (-40C to +40C)

Life: 50,000 hours L70 **Voltage:** 120-277V

Dimming: 120V TRIAC dimming option

Warranty: 120V: 1 Years carefree for parts & components

(labor not included)


120-277V: 1 Years carefree for parts & components

(labor not included)

Listings: cETLus listed for wet location, Energy Star rated,

Assembled in the USA





ORDERING INFORMATION Example: (16007-23W-40K-BK)

| Model | Wattage Lumens Dimming Voltage | Color Temperature | Housing Finish |
|-------|---|---------------------|----------------------|
| 16007 | 23W 23 Watts 1900 Lumens Triac Dimming 120V 22W 22 Watts 1824 Lumens Non-Dimming 120V- 277V | 30K 3000K | - WH White |
| | | 40K 4000K | BK Black |