

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

Cast downlighting in a storage, parking or shopping space—or in a walkway or entrance. Our modern, commercial-grade canopy light offers a low-profile design and vandal-resistant lens in a powder-coated metal finish.

FEATURES

Dimensions: L-12.1" x W-12.1" x H-4.25"

Construction: Welded aluminum profile

Finish: Powder-coated for indoor and outdoor applications

Voltage: 120-277V

Dimming: 0-10V dimming driver is standard

Lens: Vandal-resistant polycarbonate

Low Operating Temperature: -20C to +50C (-4°F to 122°F)

Listings: ETL listed, DLC premium, Wet Location suitable, Made in America

Warranty: 5 years carefree for parts & components (labor not included)



Alcon 16008 Architectural Low-Profile Aluminum Canopy LED Light



ORDERING INFORMATION Example: (16008-26W-40K-WH-OS)

Model	Wattage & Lumens	Color Temp	Finish	Options
16008	14W 14 watts 1709 lms	30K 3000K	WH <small>Standard</small> White	PH Photocell
	20W 20 watts 2519 lms	35K 3500K	BZ <small>Standard</small> Bronze	OS Occupancy Sensor
	26W 26 watts 3372 lms	40K 4000K	SL Silver	EM Emergency Battery
	31W 31 watts 4175 lms	50K 5000K	BK Black	
	38W 38 watts 4875 lms			