## SPECIFICATION SHEET



Project Name:	Type:	Quantity:

## INTENDED USE

Cast low-profile LED lighting with this durable exterior wallpack light for industrial parks or shopping centers, as well as campus, office and medical buildings, in a powder-coated finish with a vandal-resistant lens. Gain clear, modern lighting for low-level security space.

## **FEATURES**

Dimensions: L-12.3" x W-12.3" x H-4.3" Construction: Fully gasketed aluminum profile

Finish: Powder-coated for indoor and

outdoor applications

LED Driver: 120-277V input, 0-10V LED

dimming driver is standard Surge Protection: 2.5 KV surge

protection standard

Lens: Vandal-resistant polycarbonate

lens with prism pattern

Low Operating Temperature: -20C to

+50C (-4°F to 122°F) Life: 50,000 hour lifetime

Listings: ETL listed, Wet Location

suitable. Made in America

Warranty: 5 years carefree for parts & components (labor not included)











Model Wattage & Lumens Color Temp **Options Finish** WH Standard 16009 PH 30K 3000K White 120-277V 14 watts | 1249 lms Photocell 35K 20W 20 watts | 1918 lms 3500K ΒZ Bronze 26 watts | 2503 lms SL Silver 40K 4000K OS Occupancy 31W 31 watts | 3117 lms BK Sensor **50K** 5000K Black 38W 38 watts | 3611 lms **EM Emergency Battery** 



