

FEATURES & SPECIFICATIONS

INTENDED USE


Architectural Fluorescent linear fixture for distinctive architectural lighting plans. Ideal for corridors, lobbies, and office areas. Linear fixtures can be installed individually or in group patterns.

SIZE

Length: 2 ft  
Width: 7.25"  
Height: 3"

ADDITIONAL FEATURES

- Housing is made of die-formed 20 gauge cold-rolled steel
- Parabolic semi-specular aluminum louvers with flat steel end plate is standard
- UL listed for dry and damp location
- 0-10V Dimming option
- UNV 120V-277V
- ARRA compliant



Listings:



Ordering Information:

Example: (6020-2-1-17)

| Model  | Wattage Package                               | Finish               | Options                                   |
|--------|---|----------------------|---|
| 6020-2 | 1-17<br>1 Lamp 17 Watt T8                     | Blank<br>Matte White | DM7<br>0-10V Mark7 Dimming                |
|        | 2-17<br>2 Lamp 17 Watt T8<br>(34 Total Watts) | AL<br>Light Gray     | MS<br>Occupancy Sensor                    |
|        | 1-14<br>1 Lamp 14 Watt T5                     |                      | DL<br>Damp Location Label                 |
|        | 2-14<br>2 Lamp 14 Watt T5<br>(28 Total Watts) |                      | EM500<br>Emergency Ballast<br>(500 lum)   |
|        |   |                      | EM800<br>Emergency Ballast<br>(800 lum)   |
|        |   |                      | EM1300<br>Emergency Ballast<br>(1300 lum) |