

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Fluorescent Indoor Modern Architectural Linear Wall Mount - Direct/Indirect** delivers continuous clean lines and clear wall light to commercial, hospitality and residential interior wall lighting applications. Our slim profiles and stylish modern wall sconces offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

DIMENSIONS

8FT | W 7.25" x L 96" x H 3"

FEATURES

Construction: Die-formed 20 gauge cold-rolled steel. Parabolic semi-specular aluminum louvers with flat steel end plate is standard.

Reflector: Die-formed high-reflective white reflector with flat steel end plate

Light Distribution: 5% down, 95% up

Dimming: 0-10V option


Voltage: 120-277V

Color Temperature: 3000K

CRI: 80+

Warranty: 3 years carefree for parts & components (Labor not included)

Listings: UL listed for dry and damp location, ARRA compliant



ORDERING INFORMATION Example: (6020-8-2-32)

Model	Wattage Package	Finish	Options
6020-8	2-32 2x1 Lamp 17 Watt T8 (64 Total Watts)	Blank AL Matte White Light Gray	DM7 0-10V Mark7 Dimming
	4-32 4x1 Lamp 17 Watt T8 (128 Total Watts)		MS Occupancy Sensor
	2-54 2x1 Lamp 14 Watt T5 (108 Total Watts)		DL Damp Location Label
	4-54 4x1 Lamp 14 Watt T5 (216 Total Watts)		EM500 Emergency Ballast (500 lum)
			EM800 Emergency Ballast (800 lum)
			EM1300 Emergency Ballast (1300 lum)