

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Fluorescent Indoor Modern Architectural Linear Wall Mount - Direct/Indirect** delivers continuous clean lines and clear wall light to commercial, hospitality and residential interior wall lighting applications. Our slim profiles and stylish modern wall sconces offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

AVAILABLE LENGTHS

2FT	W	7.25"	x	L	24"	x	H	3"
3FT	W	7.25"	x	L	36"	x	H	3"
4FT	W	7.25"	x	L	48"	x	H	3"
8FT	W	7.25"	x	L	96"	x	H	3"

FEATURES

Construction: Die-formed 20 gauge cold-rolled steel

Reflector: Die-formed high-reflective white reflector with flat steel end plate

Light Distribution: 5% down, 95% up

Dimming: 0-10V option

Voltage: 120-277V


Color Temperature: 3000K

CRI: 80+

Warranty: 3 years carefree for parts & components
(Labor not included)

Listings: UL listed for dry and damp location, ARRA compliant

Lamps not included



ORDERING INFORMATION Example: (6021-3-1-25)

Model	Wattage Package	Finish	Options
6021-3	1-25	1 Lamp 25 Watt T8	DM7 0-10V Mark7 Dimming MS Occupancy Sensor DL Damp Location Label EM500 Emergency Ballast (500 lum) EM800 Emergency Ballast (800 lum) EM1300 Emergency Ballast (1300 lum)
	1-21	1 Lamp 21 Watt T5	
	2-25	2 Lamp 25 Watt T8 (50 Total Watts)	
	2-21	2 Lamp 21 Watt T5 (42 Total Watts)	
		Blank Matte White AL Light Gray	

6021-3 Fluorescent Indoor Modern Architectural 3 Foot Linear Wall Mount - Direct/Indirect