

Project Name:

Type:

Quantity:

FIXTURE SPECIFICATIONS

INTENDED USE

The specification grade **Fluorescent Indoor Modern Architectural Linear Wall Mount - Direct/Indirect** delivers continuous clean lines and clear wall light to commercial, hospitality and residential interior wall lighting applications. Our slim profiles and stylish modern wall sconces offer excellent direct and indirect lighting, exceptional performance and versatility in offices, classrooms, conference rooms, museums, retail outlets, hotels, restaurants, and more.

AVAILABLE LENGTHS

2FT	W	7.25"	x	L	24"	x	H	3"
3FT	W	7.25"	x	L	36"	x	H	3"
4FT	W	7.25"	x	L	48"	x	H	3"
8FT	W	7.25"	x	L	96"	x	H	3"

FEATURES

Construction: Die-formed 20 gauge cold-rolled steel

Reflector: Die-formed high-reflective white reflector with flat steel end plate

Light Distribution: 5% down, 95% up

Dimming: 0-10V option

Voltage: 120-277V


Color Temperature: 3000K

CRI: 80+

Warranty: 3 years carefree for parts & components
(Labor not included)

Listings: UL listed for dry and damp location, ARRA compliant

Lamps not included



ORDERING INFORMATION Example: (6021-4-1-32)

Model	Wattage Package	Finish	Options
6021-4	1-32 1 Lamp 32 Watt T8	Blank Matte White	DM7 0-10V Mark7 Dimming
	1-54 1 Lamp 54 Watt T5	AL Light Gray	MS Occupancy Sensor
	2-32 2 Lamp 32 Watt T8 (64 Total Watts)		DL Damp Location Label
	2-54 2 Lamp 54 Watt T5 (108 Total Watts)		EM500 Emergency Ballast (500 lum)
			EM800 Emergency Ballast (800 lum)
			EM1300 Emergency Ballast (1300 lum)

6021-4 Fluorescent Indoor Modern Architectural 3 Foot Linear Wall Mount - Direct/Indirect