## SPECIFICATION SHEET

Shop Now

Project Name:	Type:	Ouantity:
· - <b>y</b> · · · - · · - ·	1,500.	Qualitity!

## INTENDED USE

The stainless steel, multipurpose LED uplighting is made to last for residential and commercial use. Our architectural product includes an anti-moisture migration connection. The light's seal-tight waterproof enclosure and warm white color temperature also make this corrosion-resistant fixture perfect for proper landscape uplighting of pathways, trees and shrubs.

## **FEATURES**

**Construction:** 316 Marine Grade Stainless Steel Face Plate. Injected molded composite housing for high UV stability.

Adjustability: Fixture socket tilts for  $\pm$  25° Lens: Clear and heat resistant flat glass Color Temperature: 2700K Warm White

Mounting: Mount in-ground direct burial or concrete

encasement Voltage: 12V AC/DC Dimmable

**CRI**: 80

Ambient Temperature: -22F° to +122F° Lumens: 270 Lumens (3.5 Watts) and 470 Lumens (5 Watts)

Warranty: Limited Lifetime Warranty on Fixture

Stainless Steel face plate only.


10 year Warranty on Housing against manufacturer's


defects; 5 year Warranty on LED

3' 18-2 SJTW Burial Cord comes standard.

Remote 12V transformer required, may be ordered separately.













Ordering Information: Example: (9028-SS-3)

Model

Color Temperature

Beam Spread

Options

9028-SS

3 3.5 Watts

38° Flood

F1

CP Concrete Pour Kit

5 5 Watts

WF<sup>1</sup> 60° Wide Flood

1 Option Only Available for 5 Watt Fixture.